NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

CLACK 014754

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JAN 16 1973 STATE ENGINEER SALEM, OREGON

State Well No. 3S/4E-28 ad

State Permit No.

(1) OWNER:
Name Allan Morris
Address Rt 3 Box 1720 Estacada

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
D[redacted] [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:
Threaded [ ] Welded [X]
6" Diam. from 0 ft. to 40 ft. Gage .250
" Diam. from ft. to ft. Gage
[redacted]" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? [ ] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [ ] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [X] No If yes, by whom?
[redacted] gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 16 gal./min. with 18 ft. drawdown after 1 hrs.
[redacted]ian flow g.p.m.
Temperature of water 51° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement + 5% Bentonit-
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 8 sacks
Number of sacks of bentonite used in well seal 1/2 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [ ] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [ ] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number
SE ¼ NE ¼ Section 28 T. 3S R. 4E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 43 ft.
Static level 22 ft. below land surface. Date 10-28-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 51 ft. Depth of completed well 48 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Overburden	0	4	
Clay Red	4	12	
Clay Red w/Boulders	12	14	
Clay Red	14	38	
Clay Brown	38	48	43
Gravel Small	48	51	22

Work started 10-27-72 19 Completed 10-28 19 72
Date well drilling machine moved off of well 10-30 19 72

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Don. Foreman (Drilling Machine Operator) Date 10/30, 1972
Drilling Machine Operator's License No. 231

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name F+S Well Drilling (Person, firm or corporation) (Type or print)
Address Rt-3-Box 489 Estacada
[Signed] Donald Foreman (Water Well Contractor)
Contractor's License No. 477 Date 10/30, 1972

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119