NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

CLAC 015048

015048

State Well No. 5/8-25

State Permit No.

(1) OWNER:

Name United States Dept of Agriculture

Address U S Forest Service P O Box 3233
Portland 10, Oregon

(2) LOCATION OF WELL:

County Clackamas Driller's well number

¼ ¼ Section 25 T. 5S R. 8E W.M.

Bearing and distance from section or subdivision corner

Timothy Lake Campground #C

(3) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 26 ft. Gage .280

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(8) SCREENS: Well screen installed ☐ Yes ☒ No

Manufacturer's Name

Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Bentonite & Cement

Depth of seal 26' ft. Was a packer used? Yes

Diameter of well bore to bottom of seal 9 in.

Were any loose strata cemented off? ☐ Yes ☒ No Depth

Was a drive shoe used? ☒ Yes ☐ No

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? Depth of strata

Method of sealing strata off

(10) WATER LEVELS:

Static level 45 ft. below land surface Date 12/10/63

Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Bailer test 30 gal./min. with 0 ft. drawdown after 3 hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing 6 0

Depth drilled 78 ft. Depth of completed well 78 ft.

Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
~~Decayed material & topsoil~~		
Clay and broken rock	0	9
Brocken rock-no clay	9	15
Broken rock	15	24
Fractured Basalt	24	34
Solid Basalt	34	40
Grey Basalt-Crevices	40	52
Grey Basalt	52	75
Fractured Rock-water bearing	75	78

Work started 11/27 19 63 Completed 12/12 1963

Date well drilling machine moved off of well 12/13 19 63

(13) PUMP:

Manufacturer's Name Deming Handpumps

Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME A. M. Jannsen Drilling Co. (Person, firm or corporation) (Type or print)

Address 21075 S W T.V. Hiway Aloha, Oregon

Drilling Machine Operator's License No. 236

[Signed] Edward O. Jannsen (Water Well Contractor)

Contractor's License No. 79 Date 2/25, 19 63

(USE ADDITIONAL SHEETS IF NECESSARY)