WATER WELL REPORT STATE OF OREGON

REGEIVED

JUN 1 7 1993

State Well No. 6S-1E-5

WATER RESOURCES DEPT.State Permit No.

SALEM, OF CON

(1) OWNER:	(10) LOCATION OF WELL:
Name Dan Kintz	County Clackamas Driller's well number
Address 7501 S. Drake Rd.	SN 4 SE 4 Section 5 T. 6S R. 1E W.M.
City Mt. Angel State Or.	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Same as mailing
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 161 ft.
TYPE OF WELL: (4) PROPOSED USE (check):	Static level 52 ft. below land surface. Date 5-15-83
notary Air 🔘 Driven 🔘 Domestic 🔘 Industrial 🗎 Municipal 🗆	Artesian pressure lbs. per square inch. Date
Rotary Mud	(12) WELL LOG: Diameter of well below casing6.
CASING INSTALLED: Steel Plastic Welded Welded Welded 250 Plastic Plastic	Depth drilled 200 ft. Depth of completed well 200 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: none	MATERIAL From To SWL
"Diam. from ft. to ft. Gauge	Soil med brown 0 1
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No	Clay sticky brown 1 7
Type of perforator used	Clay med brown 7 16
Size of perforations in. by in.	Conglm. med-lge brn 16 30
perforations from	Clay sticky grey 30 67
perforations from ft. to ft.	Claystone brn. 85 102
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Claystone hard, grey 102 128 Clay, yellow-brn med 128 139
Manufacturer's Name	Claystone, grey, sandstn
Type	strks, grey 139 200 WB
Diam. Slot Size Set from ft. to ft.	Boins, Frey
Diam. Slot Size Set from ft. to ft.	
WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ౫ No If yes, by whom?	
ld: gal./min. with ft. drawdown after hrs.	
V II	
test 30 gal./min. with drill stem at 200 ft. $1\frac{1}{4}$ hrs.	
bailer test gal./min. with ft. drawdown after hrs.	
tesian flow g.p.m.	
emperature of water Depth artesian flow encountered ft.	Work started 6-11 19 83 Completed 6-15 1983
(9) CONSTRUCTION: Special standards: Yes □ No □	Date well drilling machine moved off of well $6-15$ 1983
Well seal—Material used Cement & bent.	Drilling Machine Operator's Certification:
Well sealed from land surface to 147 ft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal in.	and information reported aftove are true to my best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Standard Date -16, 19.83
Number of sacks of cement used in well seal 16, 5 bent. sacks	Drilling Machine Operator's License No.
How was cement grout placed? DUMDED	
5 Saciss Cement @ 147' - bent UP to	Water Well Contractor's Certification:
25'- Cement to Surface	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name West Coast Drilling Co. Inc.
Was a drive shoe used? ☐Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐No	(Person, firm or corporation) (Type or print)
Type of Water? depth of strata	Address 220 Agademy Stylet Angel. Or.
Method of sealing strata off	[Signed] hull May
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor) Contractor's License No. 7.3 Date 6-16-83 19.83
Gravel placed from	Contractor's License No. 25 Date 6-16-83 , 19.83
	<u> </u>