

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report  
are to be filed with the

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

RECEIVED WATER WELL REPORT  
STATE OF OREGON AUG 14 1978  
WATER RESOURCES DEPT. SALEM, OREGON  
AUG 28 1978  
(Please type or print)  
Do not write above this line

State Well No. 6511E-5dc

Permit No. CLAC 015149

(1) OWNER:

Name Greg Tipikan  
Address RT. 1 Box 52  
Mt. Angel, Ore. 97362

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
Dug  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

CASING INSTALLED:

Threaded  Welded

8" Diam. from 0 ft. to 138 ft. Gage 250  
" Diam. from " ft. to " ft. Gage  
" Diam. from " ft. to " ft. Gage

PERFORATIONS:

Perforated?  Yes  No.

Type of perforator used  
Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No

Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made?  Yes  No If yes, by whom? driller  
Yield: 280 gal./min. with 21 ft. drawdown after 3 hrs.  
" " " "  
" " " "  
Bailer test gal./min. with ft. drawdown after hrs.  
Artesian flow g.p.m.  
Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement  
Well sealed from land surface to 138 ft.  
Diameter of well bore to bottom of seal 12 in.  
Diameter of well bore below seal 8 in.  
Number of sacks of cement used in well seal 49 sacks  
How was cement grout placed?

Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 84  
S1/4 SE 1/4 Section 5 T. 6S R. 1E W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 194 ft.  
Static level 97 ft. below land surface. Date 7-14-78  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 245 ft. Depth of completed well 245 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
Clay, brown	2	6	
Clay, sand, brown, fine	6	10	
Clay, blue	10	22	
Gravel, cemented	22	29	
Clay, brown	29	38	
Clay, sand, blue, fine	38	56	
Clay, blue	56	69	
Clay, brown	69	133	
Shale	133	194	
*Shale, fract.	194	245	

Work started 7-7 1978 Completed 7-14 1978  
Date well drilling machine moved off of well 7-14 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Bob Kern Date 7-28, 1978.  
(Drilling Machine Operator)

Drilling Machine Operator's License No. 994

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name B. & G. Drilling  
(Person, firm or corporation) (Type or print)

Address 10030 S. Macksburg Rd. Canby, Ore.

[Signed] George Wainwright  
(Water Well Contractor)

Contractor's License No. 637 Date 7-28, 1978