ATER WELL REPORT STATE OF OREGON

CLAC 015301

RECEIVED State Well N DEC 18 1981

lo.	105/2E	-3 bc
	1	

WATER RECOURCES DEPONING

(1) OWNER:	(10) LOCATION OF WELL:	' —	
Name Totem Village Mobile Park	County Clackamas Driller's well	number	
Address 36451 S. Sawtell Rd.	5.ω 4 N.ω 4 Section 3 T. 6 S	R. 2 E W.	<u>M.</u>
City Mollala , OR 97038 State	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location: Same as item	# 1	
New Well □ Deepening ■ Reconditioning □ Abandon □			_
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 2.87		ft.
		and surface. Date 11 -9-8	31
Rotary Mud	Artesian pressure lbs. pe	er square inch. Date	
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below	casing 6"	
CASING INSTALLED: Steel M Plastic	Depth drilled		
Threaded Welded T	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry		
6" Diam from ORIGINAL 3/ ft Gauge . 250	for each change of formation. Report each change in		
"Diam. from ft. to ORIGINAL Gauge ORIGINAL	and indicate principal water-bearing strata.	<u></u>	
LINER INSTALLED:	MATERIAL	From To SWL	
$4\frac{1}{3}$ " Diam. from $+1$ ft. to 307 ft. Gauge 160. lb. test	Basalt grey hard	241 243	_
(6) PERFORATIONS: Perforated? ☑ Yes ☐ No	Basalt grey hard crevacy	243 256	_
Type of perforator used Portable electric circular saw	Claystone grey medium	256 277	
Size of perforations $\frac{1}{8}$ in. by $6\frac{1}{2}$ in.	Basalt grey hard crevacy	277 285	
112 perforations from 207 ft. to 307 ft.	Basalt grey-brown hard W.B.	285 307 207	—
perforations from ft. to ft.			
perforations from ft. to ft.		 	
(7) SCREENS: Well screen installed? Yes X No		 	_
Manufacturer's Name			—
Type		 	
Diam. Slot Size Set from ft. to ft.		 	
Diam. Slot Size Set from ft. to ft.	· · · · · · · · · · · · · · · · · · ·		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			_
			_
Was a pump test made? ☐ Yes X No If yes, by whom?			
dd: gal./min. with ft. drawdown after hrs.		 	—
Air test 42½ gal./min. with drill stem at 306 ft. 1 hrs		 	
Bailer test gal./min, with ft. drawdown after hrs.			—
Batter test gar./min. with 10. drawdown arter in s.		 	
nperature of water Depth artesian flow encountered ft.		- 44 0 94	—
		ed 11-9-81 19	—
(9) CONSTRUCTION: Special standards: Yes □ No 🖔 ORIGINAL		11-9-81 19	—
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my direct s and information reported above are true to my b		
Diameter of well bore to bottom of sealin. Diameter of well bore below sealin.		Date11-30, 198	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	- •	
How was cement grout placed?	Drilling Machine Operator's License No. 1454	ý	•••
TOW WED COLOR BLOW PLACES.	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction	n and this report is true	e to
Was pump installed?	the best of my knowledge and belief.		
Was a drive shoe used? ☐ Yes 🏅 No Plugs Size: location ft.	Name R. Stadeli & Sons, Inc. (Person, firm or corporation)	(Type or print)	•••
Did any strata contain unusable water? □ Yes 🏌 No	Address 11364 Evgrn Rd NE Silver		•••
Type of Water? depth of strata	DIO St Int		
Method of sealing strata off	[Signed] (Water Well Contract		•••
Was well gravel packed? ☐ Yes X No Size of gravel:	Contractor's License No. 296 Date 12:	- <i>3 - 81</i> , 19 .	
Gravel placed from ft. to ft.		•	