

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

RECEIVED

NOV 12 1974

State Well No.

65/6E-1566

STATE ENGINEER

State Permit No.

SALEM, OREGON

CLAC 015536

(1) OWNER:

Name U.S. Dept. of Agriculture-Forest Service Address 2440 S. E. 195th, Portland, Or. 97223

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 42 ft. Gage 0.250

PERFORATIONS:

Perforated? [X] Yes [] No. Slotted with cutting torch. 12 perforations from 35 ft. to 41 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No. Manufacturer's Name, Type, Model No., Diam., Slot size, Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [] Yes [X] No. Yield: gal./min. with ft. drawdown after hrs. Bailer test 1 1/2 gal./min. with 136 ft. drawdown after 2 hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement grout. Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 10 in. to 42 ft. Number of sacks of cement used in well seal 21 sacks. Number of sacks of bentonite used in well seal sacks. Brand name of bentonite. Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [X] Yes [] No. Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No. Type of water? depth of strata. Method of sealing strata off. Was well gravel packed? [X] Yes [] No. Size of gravel: 3/4" minus. Gravel placed from 20 ft. to 42 ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 56-74 NW 1/4 NW 1/4 Section 15 T. 6S R. 6E W.M. Bearing and distance from section or subdivision corner Riverside Campground

(11) WATER LEVEL: Completed well.

Depth at which water was first found 30 ft. Static level 14 ft. below land surface. Date 10/14/74 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 inch. Depth drilled 150 ft. Depth of completed well 150 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Clay, brown, sandy; Gravel and boulders, cemented; Rock, blue-med. hard; Rock, grey-med. hard; Rock, bluish grey, med. hard.

Work started Sept. 19 19 74 Completed Oct. 14 19 74 Date well drilling machine moved off of well Oct. 15 19 74

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Robert E. McConnell Date Oct. 16, 1974 (Drilling Machine Operator)

Drilling Machine Operator's License No. 68

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Steinman Bros. (Person, firm or corporation) (Type or print)

Address 14912 S. E. Kellogg Ave., Milwaukie, Or. 97222

[Signed] Robert E. McConnell (Water Well Contractor)

Contractor's License No. I Date Oct. 16, 1974