WATER WELL REPORT STATE OF OREGON

NOV 31980

RECEIVED

CLAC

WATER RESOURCES DEPT. SALEM, OREGON

State Well No. 65 (15538

(1) OWNER:	(10) LOCATION OF WELL:		
Name Portland General Electric Company	County Clackamas Driller's well num	aber 38-80	
Address 121 S. W. Salmon Street	N ½ x S ½ x Section h T. 6-S R.	7-E W.M.	
City Portland State Oregon	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location:		
	Lake Harriet		
New Well Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found 36	ft.	
TYPE OF WELL: (4) PROPOSED USE (check):		urface. Date 10-15-80	
Rosery Air Driven Domestic Industrial Municipal	Artesian pressure lbs. per square inch. Date		
Rotary Mud	(12) WELL LOG: Diameter of well below casir		
CACING INCOME IND	Depth drilled 76 ft. Depth of comp	i	
CASING INSTALLED: Steel R Plastic Threaded Welded R St. "Diam. from 11 to The Gauge 250 ft. to ft. Gauge	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
LINER INSTALLED:	MATERIAL Fr	om To SWL	
	Loose clay and rock	0 27	
(a) PEPEGA		27 36	
(6) PERFORATIONS: Perforated? Type of perforator used Torch		36 76 14	
Size of perforations 1/8 in. by 12 in.			
40 perforations from 54 ft. to 73 ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(=) (CODYSTATO			
(7) SCREENS: Well screen installed? ☐ Yes ZNo Manufacturer's Name			
Type			
Diam. Slot Size Set from ft. to ft.			
Diam. Slot Size Set from ft. to ft.			
WELL TESTS: Drawdown is amount water level is lowered below static level			
es a pump test made? Yes No If yes, by whom?			
eld: gal./min. with ft. drawdown after hrs.			
H " " "			
test gal./min. with drill stem at ft. hrs.			
miler test 30 gal./min. with 36 ft. drawdown after 1 hrs.			
esian flow g.p.m.			
Temperature of water 56° Depth artesian flow encountered ft.	Work started 10-3- 19 80 Completed	10-15- 1980	
(9) CONSTRUCTION: Special standards: Yes □ No 🕱	Date well drilling machine moved off of well October		
Well seal—Material used Cement grout	Drilling Machine Operator's Certification:	•	
Well sealed from land surface toft.	This well was constructed under my direct super		
Diameter of well bore to bottom of seal10 in.	and information reported above are true to my best l	snowledge and belief.	
Diameter of well bore below seal		Date 10-25, 1980	
Number of sacks of cement used in well seal sacks	Ronald F. McConnect (1997) Drilling Machine Operator's License No398		
How was cement grout placed? Pumped through a one-inch			
plastic pipe between the six-inch casing and	Water Well Contractor's Certification:	d this non-ut is t t	
the ten-inch hole.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was pump installed? NO	Name Steinman Bros. Drilling Co.		
Was a drive shoe used? ☐ Yes ■ No Plugs	(Person, firm or corporation)	(Type or print)	
Type of Water? depth of strata	Address 3023 S. E. Holly Avenue, M	t+uanvte1 At ago.	
Method of sealing strata off	[Signed] London L. McConnell		
Was well gravel packed? ▼ Yes □ No Size of gravel: 3/1 minus	Ronald F. McConnell (Water Well Contractor) Contractor's License No	r 25 - 20	
Gravel placed from 24 ft. to 74 ft.	Contractor's License No	, 19.00	