NOTICE TO WATER WELL CONTRACTOR The original and first copy <b>DECEIV</b> WATER WEI of this report are to be <b>DECEIV</b> WATER WEI	LL REPORT GLAG	o.lor	00-
STATE ENGINEER, SALEM, OREGON 9731 UN 3 1974 (Please type)	OREGON State Well No.	35/2E-	
within 30 days from the STATE ENGINEER, ite a of well completion. SALEM. OREGON	bove this line)	01	
	(10) LOCATION OF WELL.		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Eldon Evans Address 22289 S.Molalla Highway 213	County Clackanas Driller's well number		
Address 22209 S.Molalla filghway 215 Oregon City, Oregon 97045	$\mathbf{S} \cdot \mathbf{W} \cdot \mathbf{W} \cdot \mathbf{H} \mathbf{N} \cdot \mathbf{E}_{\mathbf{Z} \text{ Section}} 28 = \mathbf{T} \cdot \mathbf{J} \cdot \mathbf{S} \cdot \mathbf{R} \cdot 2 \cdot \mathbf{E} \cdot \mathbf{W} \cdot \mathbf{M}$		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner	
New Well Deepening Reconditioning Abandon	·····		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) <b>TYPE</b> OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 12 ft.		
Rotary     Main     Driven     Domestic     Industrial     Municipal       Cable     Detted     Domestic     Industrial     Municipal	Static level 13 ft. below land surface. Date 5/15/74		
Dug Bored I Irrigation K Test Well Other	A		
	Artesian pressure XX lbs. per squar	c men. Dute	
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well below casingO		
8 " Diam. from 1+ ft. to 268 ft. Gage .250	Depth drilled 274 ft. Depth of compl	~	ft.
	Formation: Describe color, texture, grain size a		
ft. to ft. Gage	and show thickness and nature of each stratur	n and aquifer per	netrated,
PERFORATIONS: Perforated? EKVes CI No.	with at least one entry for each change of format position of Static Water Level and indicate prin		
Type of perforator used POWET SAW	MATERIAL	From To	SWL
Size of perforations 3/16 in. by 2-1 in.	Tep seil-brn.	0 1	
5760 perforations from 18 ft. to 268 ft.	<u>Clay-brn.</u>	1 10	
perforations from ft. to ft.	Sandstene, brn.& red	10 32	
ft. to ft.	Basalt Grey-	32 48	<u></u>
(7) SCREENS: Well screen installed?  Ves X No	<u>Clay-brn.</u>	48 51	
Manufacturer's Name	Sandstone-brn.	51 96	
Type	<u>Clay-brn.</u>	96 101	
Diam. Slot size	Sandstone-brn.	101 122 122 140	
Diam. Slot size	Sandstone-grey Sand-grey	122 140 140 142	<u> </u>
	Clay-grey & sticky	142 197	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sandstene-grey, med.hd.		(W.B)
Was a pump test made? [] Yes X No If yes, by whom?	Clay-sticky, grey	071 001	
	Sandstone-grey hd.		(W.B)
Yield: gal./min. with ft. drawdown after hrs.	Clay-sticky.grey	259 274	
<u>Air</u> " " "	Bettem 10 ft.of casing is	filled	
BXX test 120 gal./min. with ft. drawdown after hrs.	back with gravel.		·····
Artesian flow g.p.m.	*		······································
perature of water Depth artesian flow encountered ft.	Work started 4/5/74 19 Complete	a 5/15/74	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5/15/74	19
(levent			
Well sealed from land surface to 18 ft	Drilling Machine Operator's Certification: This well was constructed under my	direct super-	vision
	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
	best knowledge and belief.		
Diameter of well bore below seal in.	[Signed] Challes Startley Date 5/31, 1974		
Number of sacks of cement used in wen sear	Drilling Machine Operator's License No. 7.20		
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdi	ction and this re	eport is
of water	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🖸 Yes 🎝 No	Name R.Stadeli & Sens, Inc.		
	(Person, firm or corporation) (Type or print) Address Rte.3, Bex 169, Silverten, Ore.97381		
Type of water? XX depth of strata	Address RCC.5, Bex 109, S11Verten, Ore.97381		
Method of sealing strata off XX	[Signed] Laul R. Stadeli		
Was well gravel packed? X Yes No Size of gravel: 3/8 to	(Water Well Contra		
Gravel placed from 268 ft to 18 ft.	Contractor's License No. 296 Date 5	/31/74	, 19
(USE ADDITIONAL SE	LEETS IF NECESSARY)	SP	*45656-119

----