

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED SEP 21 1970 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

Do not write above this line

CLAC 16577 C5580

State Well No. 3/3-700 State Permit No.

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

(1) OWNER:

Name William Carr Address 3508 S. E. Roswell, Milwaukie, Or. 97222

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

8" Diam. from 0 ft. to 186 ft. Gage 0.250 6" Diam. from 181 ft. to 221 ft. Gage 0.250

PERFORATIONS:

Type of perforator used Torch Size of perforations 1/8 in. by 12 in. 12 perforations from 182 ft. to 197 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No Yield: gal./min. with ft. drawdown after hrs. Bailer test 20 gal./min. with total ft. drawdown after 1 hrs. Artesian flow g.p.m. Temperature of water 54.9 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite and drill cuttings Well sealed from land surface to 76 ft. Diameter of well bore to bottom of seal 12 in. Number of sacks of cement used in well seal None Number of sacks of bentonite used in well seal One Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [x] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 50-70 NW 1/4 NE 1/4 Section 7 T. 3S R. 3E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 194 ft. Static level 132 ft. below land surface. Date 9-14-70 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 225 ft. Depth of completed well 221 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Clay, sticky, brown; Clay, sandy, tan; Clay, sandy, orange; Rock and clay, grey; Clay, brown; Sandstone, brown; Clay, tan; Clay, blue; Sand, grey; Clay, blue; Silt, grey; Clay, blue; Gravel and sand; Clay, blue; Clay, grey.

Work started Sept. 3 1970 Completed Sept. 14 1970 Date well drilling machine moved off of well Sept. 15 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Ronald L. McConnell Date Sept. 18 1970 Drilling Machine Operator's License No. 398

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Steinman Bros. Address 14912 S.E. Kellogg, Milwaukie, Or. 97222 [Signed] Robert E. McConnell Date Sept. 18 1970 Contractor's License No. 1 Date Sept. 18 1970