NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date of well completion.

CLAC 16977

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 3S/3E-26
State Permit No.

(1) OWNER:
Name Bob ATKINSON
Address RT 2 Box 1002 Estacada Ore

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from 0 ft. to 60 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used TORCH
Size of perforations 1/8 in. by 6 in.
45 perforations from 40 ft. to 60 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 6 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement grout
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed? Cement was Place with trimie Pipe & Pressure grouted from 25 feet to of land surface
Was a drive shoe used? ☑ Yes ☐ No Plugs Size location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☑ Yes ☐ No Size of gravel: 3/4
Gravel placed from 60 ft. to 25 ft.

(10) LOCATION OF WELL:
County Clack Driller's well number
¼ ¼ Section 26 T. 3S R. 3E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 45 ft.
Static level 28 ft. below land surface. Date Aug 11 79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 60 ft. Depth of completed well 60 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	0
Sandy Yellow Clay	2	9	0
Gravel & Boulders	9	14	0
Clay Brown	14	45	28
Coarse Sand & Gravel WB	45	56	28
Blue Clay	56	60	28

RECEIVED
AUG 15 1979
WATER RESOURCES DEPT
SALEM, OREGON

Work started Aug 4 1979 Completed Aug 11 1979
Date well drilling machine moved off of well Aug 11 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Brad Brad (Drilling Machine Operator) Date Aug 14, 1979
Drilling Machine Operator's License No. 861

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name LAHZ WELL Drilling (Person, firm or corporation) (Type or print)
Address 15702 S. Neiber Rd. Oregon City
[Signed] Donald O Lahz (Water Well Contractor)
Contractor's License No. 565 Date 8-14, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119