WATER WELL REPORT

LEAG		8		
AND	' \	31	3 all	1
1070	State W	ell No. 3/	2724	4
		/		

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date TATE ENGINEER

of well completion.

SALEM. OREGON

(11) LOCA

State Permit No. ..

SATEON .		
(1) OWNER:	(11) LOCATION OF WELL:	
Name MILAS W. MILLER	County CLACK Driller's well number 108	3
Address 1646 BUCK ST WESTLINDORE.	NW 14 SW 14 Section 34 T. 35 R. 3E	W.M.
	Bearing and distance from section or subdivision corner	,
(2) TYPE OF WORK (check):		
New Well K Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	:	<u> </u>
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing	consum y
Cable	Depth drilled 85 ft. Depth of completed well 8	C ft.
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Formation: Describe color, texture, grain size and structure of	~
(5) CASING INSTALLED: Threaded □ Welded	and show thickness and nature of each stratum and aquifer	penetrated,
6 " Diam. from 0 ft. to 85 ft. Gage , 360	with at least one entry for each change of formation. Report ein position of Static Water Level as drilling proceeds. Note dri	ach change
" Diam. from ft. to ft. Gage		
" Diam. fromft. toft. Gage	MATERIAL From To	SWL
	How or the How Const	-
(6) PERFORATIONS: Perforated? Yes No.	70P Soil 0 /	
Type of perforator used	BAULDERS AND KED CLAY 18	
Size of perforations 3/16 in. by 12 in.	BOULDERS AND YELLOW CLAY 8 32	
80 perforations from 45 ft. to 75 ft.	BOULDERS AND RED CLAY 32 60	177
perforations fromft. toft.	SOFT ROCK 60 50	46
perforations fromft. toft.	HARD GREY ROCK 80-85	16
perforations from ft. to ft.		♥
perforations fromft. toft.	3.44	
(7) SCREENS: Well screen installed? West Yes No		
Manufacturer's Name		-
Type Model No.	de la companya de la	
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WATER LEVEL: Completed well.		
Static level /6 ft. below land surface Date 4/39/70		-
sian pressure lbs. per square inch Date		
(9) WELL TESTS: Drawdown is amount water level is		
lowered below static level		
Was a pump test made? Yes No If yes, by whom?	Washington Dags 52 man	
Yield: gal./min, with ft. drawdown after hrs.	Work started APR 339 70Completed APR 20	9 19/0
"	Date well drilling machine moved off of well APR 29	1970
n n n n n n n n n n n n n n n n n n n	Drilling Machine Operator's Certification:	
Bailer test 2.5 gal./min. with 15 ft. drawdown after 2 hrs.	This well was constructed under my direct supervision rials used and information reported above are true to	n. Mate-
Artesian flow g.p.m. Date	knowledge and belief.	my best
Temperature of water Was a chemical analysis made? ☐ Yes 📉 No	[Signed] Robert & Masser Date MAY	19 76
(10) CONSTRUCTION:	(Drilling Machine Operator)	,
Well seal-Material used CEMENT GROUT	Drilling Machine Operator's License No. 285	
Depth of seal 33	Water Well Contractor's Certification:	
Diameter of well bore to bottom of seal 10 in.	This well was drilled under my jurisdiction and this	ranort is
Were any loose strata cemented off? Yes XNo Depth	true to the best of my knowledge and belief.	report 18
Was a drive shoe used? ☐ Yes No	NAME KRIER WELL DRIVING	Co.
Did any strata contain unusable water? Tyes No	(Person, firm or corporation) (Type or print	.)
Type of water? depth of strata	Address 5365 S.E. HILLWOOD MIL	WAUKIE
Method of sealing strata off	00000	
	[Signed] (Water Well Contractor)	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)	7
Gravel placed from ft. to ft.	Contractor's License No. 102 Date 5	, 19. 10