File Original and First Copy with the STATE ENGINEER, SALEM, OREGON.



## WATER WELL REPORT STATE OF OREGON 61496

State Well No. 3/2-2/11 |
State Permit No. 6-/37/

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lowered below static level	level is
Name _ Fowley,	Was a pump test made? Yes \( \square\) No If yes, by whom? \( \sqrt{Y} \) \( \sqrt{Y} \)	
Address 5226 SE, Ivon Portland	Yield: 300 gal./min. with 29 ft. drawdown aft	er 4 hrs.
	=   " " " "	
(2) LOCATION OF WELL:	" "	**
County Clackamas Owner's number, if any	Bailer test gal./min. with ft. drawdown after	er hrs.
NW 1/4 SW 1/4 Section 2 T. 35 R. 25 W.M.		
Bearing and distance from section or subdivision corner	Temperature of water 54 Was a chemical analysis made?	☐ Yes DX6
S 85°28'59 W 454.74 feet	(12) WELL LOG: Diameter of well	8 inches.
	Depth drilled 190 ft. Depth of completed well	/80 ft.
1 400 A.So. & 600 H. East from W/ Corner	Formation: Describe by color, character, size of material and	l structure, and
Fron Z.	show thickness of aquifers and the kind and nature of the n stratum penetrated, with at least one entry for each chang	e of formation.
	MATERIAL FR	от то
(3) TYPE OF WORK (check):	Top 5011	15
New Well	ve 1/ow Clav	5 32
bandonment, describe material and procedure in Item 11.	Blue Clay	32 47
PROPOGED VICE ( I I ) (X) WALDE OF VIEW	Cament gyove)	47 52
PROPOSED USE (check): (5) TYPE OF WELL:	Blue clay 5	2 125
Domestic   Industrial   Municipal   Rotary   Driven   Cable   Jetted	Blue sand 1	15 140
Irrigation  Test Well Other Dug Bored	Sandy sydue	40 146
(C) CACING INCHALLED.	grava) with water	4/4 /50
(6) CASING INSTALLED: Threaded Welded W	course sand + grave) /	50 160
7 Diam. from 6 ft. to 6 ft. Gage 380	1 10/0/2 (5/4)/	60 165
"Diam. from		65 180
"Diam. from	b)ve clav	80 190
(7) PERFORATIONS: Perforated? The No		
Type of perforator usedi)\s\Km\te.	100 gals per comin.	
SIZE of perforations 3, y in. by in.	in Sand rock. 165-184	2
7 per defforations from 148 ft. to 155 f		
perforations fromft. tof		
perforations from ft. to ft.	1	
perforations fromft. toft.	I I	
perforations from ft. to ft.		
(8) SCREENS: Well screen installed		
Manufacturer's Name		
Type Model No		
m Slot size Set from ft. to ft.		
Slot size Set from ft, to ft	Work started 77 Y 1959 Completed 77	11 19.59
(9) CONSTRUCTION:	(13) PUMP:	·
Was well gravel packed?   Yes No Size of gravel:		
Gravel placed from ft. to ft.	. Manufacturer & Manue	******************************
Was a surface seal provided? ☐ Yes ☐ No To what depth? ft	Type: H.P.	***************************************
Material used in seal—	Well Driller's Statement:	
Did any strata contain unusable water?   Yes   No	This well was drilled under my jurisdiction and this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.	
Method of sealing strata off Cemented be on 50	21 mar A. O. Olsan	
(10) THAINED I DIVET C.	NAME (Person, firm, or corporation) (Type of	r print)
(10) WATER LEVELS: Static level 8 5 ft. below land surface Date April-	5PAddress Rt / Box 565 Syre	sham a
Artesian pressure lbs. per square inch Date	Driller's well number	
Log Accepted by:	[Signed] (C) (C)	
[Signed] TEV MU Tate 4,12, 1960	(Well Driller)	
[Signed] Date, 1964	License No. 13/252 Date May 2	4, 1959
	•	, ,