of this report are to be filed with the AUG 2 2 1972 STATE OF OREGON State Well No. 5512F-STATE ENGINEER, SALEM, OREGON 97310. ENGINEER type or print) within 30 days from the Sate A TE State Permit No. SALEM OR (Do not write above this like) of well completion. (10) LOCATION OF WELL: (1) OWNER: Clackanas Brazier Ferest Products Inc Driller's well number Name т. Address Molalla. Oregon 97038 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [Reconditioning [Abandon 🔲 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven [Rotary Domestic | Industrial | Municipal | Static level ft. below land surface. Date 8 Cable Jetted [Irrigation | Test Well | Other Bored | Dug Artesian pressure lbs. per square inch. Date 5) CASING INSTALLED: Threaded | Welded | 8 (12) WELL LOG: 260 Depth drilled ft. Depth of completed well " Diam, from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; ______ft. Gage _____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? Tyes TwNo. ype of perforator used MATERIAL Cabble rack grey in. by O Size of perforations perforations from ft. to ft. Gravel, large Cable rack ___ perforations from _____ft. to _____ft. perforations from ft. to ft. Gravel Clay with gravel, brown (7) SCREENS: Well screen installed? ☐ Yes ☐ No 58 Sand, brown Manufacturer's Name 67 137 Clay, blue Model No. Silty fermation, black 37 Slot size Set from ft. to ft. 745 Clay, with gravel Diam. Slot size Set from ... 147 Gravel with clay 754 Clay, blue, gritty Drawdown is amount water level is lowered below static level (8) WELL TESTS: Clay, brawn Sandy, black 172 27 215 Was a pump test made?
Yes No If yes, by whom? Clay, grey 228 240 gal./min. with hrs. 248 240 Clay, gritty 248 Sandy fermation 256 Sandstene, hard. 17 ft. drawdown_after Bailer test gal./min. with Artesian flow g.p.m. Depth artesian flow encountered 7/28 19 72 Completed Temperature of water Work started Date well drilling machine moved off of well **E)** CONSTRUCTION: Bentenite **Drilling Machine Operator's Certification:** Well seal-Material used This well was constructed under my direct supervision. Well sealed from land surface to ... Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal (Drilling Machine Operator) Date 8/15 , 19 72 Diameter of well bore below seal [Signed] Number of sacks of cement used in well seal ____________________________sacks Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons . This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name

C. G. Westerberg Was a drive shoe used? Z Yes D No Plugs Size: location ft. (Type or print) (Person, firm or corporation) Did any strata contain unusable water?

Yes
No Address Rt. 1. Bex 151. Muline. Oregon depth of strata Type of water? Method of sealing strata off (Water Well Contractor) Was well gravel packed? ☐ Yes ☐ No Size of gravel: 86_{Date} 8/15 , 1972 Contractor's License No. (USE ADDITIONAL SHEETS IF NECESSARY) SP*45656-119

NOTICE TO WATER WELL CONTRACTOR The original and first contractor water WELL REPORT