## NOTICE TO WATER WELL CONTACT The original and first color of this report are to be filed with the of this report are to be MAR 21 1966 STATE ENGINEER, SALEM, OREGON 97310

STATE OF OREGON

D/-	723
_	1

State	Well	No.	3/2 -	8
State	44 C11	110.		

within 30 days from the ATE ENGINEER lease type of well completion.	State Permit No
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name RUDOLPH PAVLINAC	Was a pump test made? ☐ Yes ಶ No If yes, by whom?
Address RT   Bod 690	Yield: gal./min. with ft. drawdown after hrs.
OREGON CITY	WELL MADE 200 GPM BEFORE
(2) LOCATION OF WELL:	WE REDRILLED " "
,	Bailer test NONE gal./min. with PIBO drawdown after hrs.
County CLACKAMA Coriller's well number	Artesian flow g.p.m. Date
14 Section 8 T. 35 R. 2 W.M.	Temperature of water 56 Was a chemical analysis made?   Yes No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing
	Depth drilled 562 ft. Depth of completed well 400 ft.
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(0) TUDE OF WORK (sheets).	MATERIAL FROM TO
(3) TYPE OF WORK (check):	STICKY BIVE CLAY 400 7/3
Well Deepening Reconditioning Abandon	SANDY BLUE CLAY 410 526
andonment, describe material and procedure in Item 12.	STICKY BLUE CLAY 326 335
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BROWN FINE SAND 535 540
Rotery G Driven G	TRACE OF WATER
Domestic   Industrial   Municipal   Cable   A Jetted	STICKY BLUE CLAY 540 562
Irrigation Test Well Other Dug Bored	CAVING BADLY
(6) CASING INSTALLED: Threaded   Welded	
	AS NO WATER WAS
"Diam. from NONE ft. to ft. Gage	FOUND WELL WAS NOT
OPIGIONO LASINICIO II. Gage 25	CASED' ANY MORE AND
<b>2</b> " Diam. from	PUMP REINCTALLED
(7) PERFORATIONS: Perforated? ☐ Yes   No	
- <i>n</i>	
Type of perforator used	
Size of perforations in. by in.	
perforations from	
perforations from	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes   No	
`nufacturer's Name	
Model No.	
Diam Slot size Set from ft. to ft.	Work started FFB 14 19 66 Completed FEB 18 1966
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well FEB 18 1866
(9) CONSTRUCTION:	(13) PUMP:
Well seal-Material used in seal NONE ADDED	Manufacturer's Name BERNELEY
Depth of seal NKNOWN ft. Was a packer used?	Type: TURBINE   HP 30
Diameter of well bore to bottom of seal UNAMO. WAjin.	THE ATT II COMPANY CONTRACTOR OF THE STATE O
Were any loose strata cemented off? ☐ Yes ☐ No Depth	Water Well Contractor's Certification:
Was a drive shoe used? ☐ Yes ☑ No	This well was drilled under my jurisdiction and this report is
Was well gravel packed?  Yes Y No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME WILLIAM J. STENNETT
	(Person, firm or corporation) (Type or print)
Did any strata contain unusable water? Yes No	Address 361 WARNER MILNE R.D. ORE CIT
Type of water? depth of strata	174
Method of sealing strata off	Drilling Machine Operator's License No.
(10) WATER LEVELS:	William I Standill
13/ A below land	[Signed] (Water Well Contractor)
Static level 236 ft. below land surface Date 11/06	Compression Lieunes No. 3 Parts 2/2 24 10 KM
Artesian pressure lbs. per square inch Date	Contractor's License No. Date Letter   19.0.C