NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON JUL 9 1973 State Well No. 35 2E-14	
within 30 days from the date	orgrint TE ENGINEER Permit No.
	663.57
(1) OWNER:	(10) LOCATION OF WELL:
Name W. E. ALBEKE	County CLACKAMAS Driller's well number
Address 16107 SW WILSON ROAD	SW 14 SW 14 Section 14 T. 35 R. 2E W.M.
OREGON CITY ORE.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🕺 Deepening 🗌 Reconditioning 🔲 Abandon 🗆	4
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 214 ft.
Rotary Diriven Domestic Municipal Domestic	Static level 159 ft. below land surface. Date 6/9/73
Cable IN Jetted	Artesian pressure Ibs. per square inch. Date
Dug 🗋 Bored 📋 Irrigation 🎽 Test wen 📋 Other	Ai testali pressure instruction per square instruction
CASING INSTALLED: Threaded D Welded	(12) WELL LOG: Diameter of well below casing
8 "Diam. from 0 ft. to 160 ft. Gage 7 WAL	Depth drilled $300$ ft. Depth of completed well $300$ ft.
6 " Diam. from 1110 ft to 300 ft. Gage 4"	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated? If Yes D No.	MATERIAL From To SWL
Type of perforator used TONCH	TUPCAU
Size of perforations I in. by 27 in.	VELAN CLAY 3 57
10.5 perforations from 210 ft. to 260 ft.	GREY AND BLUECLAY 57 101
perforations from ft. to ft.	ATAILOH CREY INT 160
perforations from ft. to ft.	CIAVSTONIE
(7) SCREENS: Well screen installed? 🗌 Yes 🛛 No	ALMOST BLUE SAND-160 214
Monufacturov's Nome	CTRAFE
Type*	WATER BEARING AT 214 140
Diam Slot size Set from ft. to ft.	AT ISGPHI
Diam	HARD SANDSTONE 214 234
(8) WELL TESTS: Drawdown is amount water level is	SOME CHUNTISLY 299 265
	NOW BAILS 29 GPM. 140
Was a pump test made? Yes No If yes, by whom? OWNER	STICK BLUE CLAV 265 300
gal./min. with with the drawdown after 56 hrs.	$\frac{\partial f(\alpha)}{\partial \beta} = \frac{\partial f(\beta)}{\partial \beta} = \partial $
70 " 13' " 36 "	AFTER PUMPIOLE STATIC
	WATER LEVEL 159'
Bailer test 29 gal./min. with 25 ft. drawdown after 2 hrs.	
Artesian flow g.p.m.	
berature of water 57 Depth artesian flow encounteredft.	Work started MAY 11 19 7 Ocompleted NAY 26 19 73
(9) CONSTRUCTION: HI-EARLY	Date well drilling machine moved off of well $V_{EP} A \not = 9 / 3$
Well seal-Material used 4213465 CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to6.6	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief, pa
Diameter of well bore below seal	[Signed] William Willing Machine Operator) Date June 1.2, 19.7.3
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	
Brand name of bentonite PHICK GEL	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Did any strata contain unusable water? TYes No	Name WILLIAM D. STENNETT (Person, firm or corporation) (Type or print)
Type of water? depth a strata	Address 361 WARNER MILNE RD DRE CITY
Method of sealing strata off	Willie A the ott
Was well gravel packed?  Ves X No Size of gravel:	[Signed]
Gravel placed fromft.	Contractor's License No. 3 Date Jan 12, 1873
	HEETS IF NECESSARY) SP*45658-119