NOTICE TO WATER WELL CONTRACTOR & E FOR STATE OF OREGON

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM 10, OREGON E ENGINEER

within 30 days from the date A E ENGINEER

of well completion.

0184 State Well No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level lowered below static level	el is	
Name United States Forest Service	Was a pump test made? Yes No If yes, by whom Stei		
AddressDepartment of Agriculture	Yield: 116 gal./min. with 30 ft. drawdown after	2 hrs.	
Zig Zag Ranger Sta., Zigzag, Oregon	$= \begin{vmatrix} \frac{7}{1} & \frac{75}{60} & \frac{1}{19} & \frac{1}{$	2 "	
(2) LOCATION OF WELL:			
County Clackamas Driller's well number 21-66	Bailer test gal./min. with ft. drawdown after	hrs.	
NW 1/4 NW 1/4 Section 3 T. 3S R. 7E	M. Artesian flow 10 g.p.m. Date Mar. 25, 1		
Bearing and distance from section or subdivision corner	Temperature of water 47 Was a chemical analysis made?	Yes No	
	(12) WELL LOG: Diameter of well below casing		
	Depth drilled 163ft. Depth of completed well	163 ft.	
	Formation: Describe by color, character, size of material and st. show thickness of aquifers and the kind and nature of the mate stratum penetrated, with at least one entry for each change of	rial in each f formation.	
	MATERIAL FROM		
(3) TYPE OF WORK (check):	Sandy, grey, coarse	0 2	
New Well Deepening Reconditioning Aban		2 45	
lonment, describe material and procedure in Item 12.	Grey sand and boulders and wood 4		
	Grey sand and bounders and wood 5		
(4) PROPOSED USE (check): (5) TYPE OF W	L: Sand and gravel (water)		
Domestic 🛣 Industrial 🗌 Municipal 🖂 Rotary 📮 Driver	Sand and hauldens 7		
Irrigation Test Well Rother Sta Dug Bored	Reddish-brown sand, coarse 15		
Rgr. Sta. L	Coarse gravel and sand (Artesian	TOT	
(6) CASING INSTALLED: Threaded ☐ Welded 🛣	water) 16	1 163	
	Water) to.	1 103	
ft. Gage ft. Gage			
ft. Gage ft. Gage	Manager and the same of the sa	 	
(E) DEDUCATION V			
(7) PERFORATIONS: Perforated? ☐ Yes A No Type of perforator used			
Size of perforations in. by in.			
perforations from ft. to	ft.		
perforations fromft. to	1		
perforations from ft. to			
perforations from ft. to	ft.		
perforations from ft. to			
(8) SCREENS: Well screen installed Yes Y No			
Manufacturer's Name			
Model No.			
m. Slot size <u>Set from</u> ft. to		l 1966	
Diam. Slot size Set from ft. to	ft. Date well drilling machine moved off of well April 5	1955	
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Bentonite & Cement	Manufacturer's Name		
Depth of seal 21 ft. Was a packer used? No	Type: H.P.		
Diameter of well bore to bottom of seal in.			
Were any loose strata cemented off? Tyes ANO Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 🖟 Yes 🔲 No 💮	This well was drilled under my jurisdiction and thi	s report is	
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAME Steinman Bros.		
Did any strata contain unusable water? H Yes 🗆 No (Person, firm or corporation) (Type or print)			
Type of water? Iron Depth of strata 55 to 72	Addres 5112 S.E. McLoughlin, Milwaukie, O:	re. 97222	
Method of sealing strata off Casing	Drilling Machine Operator's License No. 67		
(10) WATER LEVELS:			
Static level ft. below land surface Date	below land surface Date [Signed] (Water Well Contractor)		
Artesian pressure 5 lbs, per square inch Date 3/25/	Contractor's License No. I Date April 12	1966	
		, wow.	