

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT

NOV 14 1977

STATE OF OREGON

CLAC

01905

State Well No.

State Permit No.

35BE-150C

WATER RESOURCES DEPT.

(1) OWNER:

SALEM, OREGON

Name Mt. Hood Kiwanis Camp Inc. Address 2808 SE 65 Portland Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(10) LOCATION OF WELL:

County Clackamas Driller's well number 32 SW 1/4 NE 1/4 Section 15 T. 35 R. 8E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 39 ft. Static level 25 ft. below land surface. Date 10-28-77 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6 Depth drilled 60 ft. Depth of completed well 60 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include SAND & GRAVEL, Boulders & SAND, Rock Black, Brown Rock soft, Volcanic Rock Grey, SAND & GRAVEL & Boulders. Includes 'Completed' text.

CASING INSTALLED:

6" Diam. from 1 ft. to 35 ft. Gage 250 5.0" Diam. from 20 ft. to 60 ft. Gage 188

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used Torch Size of perforations 1/8 in. by 10 in. 60 perforations from 20 ft. to 60 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No Yield: gal./min. with ft. drawdown after hrs. Bailer test 25 gal./min. with 25 ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout Well sealed from land surface to 35 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 6 How was cement grout placed? Poured Was a drive shoe used? [] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

Work started 10-28 1977 Completed 10-29 1977 Date well drilling machine moved off of well 10-29 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Date 10-29, 1977 Drilling Machine Operator's License No. 1145

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Submersible Pump & Drilling Co. Address Rt. 1, Box 84, Hillsboro, Ore. [Signed] Date 10-29, 1977 Contractor's License No. 669 Date 10-29, 1977