STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

01906 PLEASE TYPE OF PRINT IN INK

RECEIVE 135/8E-16a SEP2 3 1985

	WATER ILL SOURCES (forgeffiqual use only)
(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name Lady Creek Water System	County Clackamas 4 NE 4 of Section 16
Address 19285 S. E. Borges Road	
City Boring State Oregon	Township 35 (Township is North or South), Range Range (Range is East or West)
	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
New Well 🔀 Deepening 🗆 Reconditioning 🗀 Abandon 🗆	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found 20
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 15 ft. below land surface. Date 9-12
Other:	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	(10) THEFT TOC
CASING INSTALLED: Steel XX Plastic	Diameter of well below casing
Threaded Welded 🖵	Depth drilled 200 ft. Depth of completed well 200 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness
8 " Diam. from +1 ft. to 177 ft. Gauge 250	and nature of each stratum and aquifer penetrated, with at least one entry for each change of
ft. to ft. Gauge	formation. Report each change in position of Static Water Level and indicate principal
LINER INSTALLED: Steel	water-bearing strata.
Threaded Welded	MATERIAL From To SWL
ft. to	Grey sand, gravel, boulders 0 11
(A) DUDUOD A TIONS	Brown sand, gravel, boulders 11 26
(6) PERFORATIONS: Perforated? Yes XX No in. by in.	Grey sand, gravel, boulders 26 42
1	Brown sand, gravel, boulders 42 49
perforations from ft. to ft.	Grey sand, gravel, boulders 49 136
perforations from ft. to ft.	Brown sand, gravel, boulders 136 153
perforations from ft. to ft.	Grey sand, gravel, boulders 153 173
(7) SCREENS: Well screen installed? Yes xx No	Lt green granite rock 173 200
Manufacturer's Name	State
TypeModel No.	
Diam Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft, to ft,	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? XX Yes No If yes, by whom? Al's Pumps	
gal./min. with 132 ft. drawdown after 2 hrs.	
II	
Air test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	
	Date work started 9-5-85 /completed 9-12-85
Special standards: Yes No XX	Date well drilling machine moved off of well 9-12-85 19
Well seal—Material usedcement + 5% Bentonite	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	
amount of sealing material	[Signed], 19,
Now was cement grout placed?pumped	(bonded) Water Well Constructor Certification:
OF A SECTION ASSESSMENT	Bond 140898 Issued by: Ore Auto Ins Co
## ***********************************	(number) (Surety Company Name)
Vas pump installed? Depth ft.	On behalf of Don Feakin (type or print name of Water Well Constructor)
Vas a drive shoe used? 🗶 Yes 🔲 No Plugs Size: location	
'ype of Water? depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:
	$\Omega = \mathcal{L}_{\mathcal{L}}$
Method of sealing strata off	(Signed) (Water Well Constructor)
Vas well gravel packed? Yes XX No Size of gravel:	(Water Well Constructor) (Dated)9-19-85
ravel placed from ft. to ft.	(