NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date

,"<u>.</u>

WATER WELL REPORT EIVED

(Please type or print)

State Permit No. ...

of well completion.	"WATER RESOURCES DEPT.		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Multopor Ski Bowl	County Clackamas Driller's well number D42-77		
Address Government Camp, Oregon, 97028	14 NE 14 Section 24 T. 3S R. 8E W.M.		
(P. Darr)			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner		
New Well Deepening □ Reconditioning □ Abandon □		· · · · · · · · · · · · · · · · · · ·	
If abandonment, describe material and procedure in Item 12.		14	
	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 35 ft.		
Rotary 🖟 Driven 🗆 Domestic 🔀 Industrial 🗆 Municipal 🗆	Static level 6 ft. below land s	urface. Date 3-17-77	
g 🛮 Bored 🖟 Irrigation 🖨 Test Well 🖂 Other 🔻	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded D Welded K			
Timedida	(12) WELL LOG: Diameter of well below casing		
8" "Diam. from +3 ft. to 176 ft. Gage .250	Depth drilled 240 ft. Depth of completed well 240 ft.		
	Formation: Describe color, texture, grain size and structure of materials;		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratur		
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prince		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Top soil	0 1	
	Conglomerate, cmtd., gravel	1	
perforations fromft. toft.	Clay, boulder, small	34	
perforations fromft. toft.	Gravel, boulder, small	34 95	
perforations from	Gravel, water	95 100	
(7) SCREENS: Well screen installed? Yes X No	Cemented, gravel	100 172	
Manufacturer's Name	Rock, soft	172 176	
Type Model No.	Rock, hard	176 210	
Diam Slot size Set from ft. to ft.	Rock, soft, water, bearing	210 230 0	
Diam Slot size Set from ft. to ft.	Rock, hard	230 240	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes \(\subseteq No \) If yes, by whom? Driller			
d: 35 gal./min. with 205 ft. drawdown after 4 hrs.			
" " "			
" " " "			
Bailer test gal./min. with ft. drawdown after hrs.			
tesian flow 2 g.p.m.			
perature of water Depth artesian flow encountered 210 ft.	Work started Mar. 9 1977 Complete	d Mar.151977	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Mar.171977	
	Duilling Weshing Oneseted Codding		
Well seal—Material usedCement_Grout	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.		
Well sealed from land surface to	Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief		
Diameter of well bore below seal in,	[Signed] (Drilling Machine Operator)	Date Mar. 219 77	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdie	ction and this report is	
of waterlbs./100 gals.	true to the best of my knowledge and belief.		
Was a drive shoe used? XYes \(\sum \) No Plugs Size: location ft.	Name S & M Drilling & Supply Inc. (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? YesXX No			
Type of water? depth of strata	Address 399 S.E. Walnut St.	.canby.ore.9701	
Method of sealing strata off	[Signed] (A)		
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contra		
Gravel placed from ft. to ft.	Contractor's License No. 497 Date	Mar. 21 137	