WATER WELL REPORT ECEIVED NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON JUL 15 1976 Permit No. 2/5/1W-1/1db (Please type or print) within 30 days from the date 01940 not write above this line ATER RESOURCES DEPT of well completion. (10) LOCATION OF WELL (1) OWNER: County MARION Driller's well number 10 NW 4 SF 4 Section // T. 45 R. / W Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well [Deepening / Reconditioning X Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Domestic | Industrial | Municipal | Static level ft. below land surface. Date Cable Jetted | Dug Bored | Irrigation Test Well [Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing ... 6 ... " Diam. from + 6 ... ft. to 78 ft. Gage 3.50 Depth drilled /04 ft. Depth of completed well " Diam. from _____ ft. to _____ ft. Gage ____ Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Tyes No. Type of perforator used MATERIAL Size of perforations in. by DRILLED ALONG SIDE 10". TO GRAVEL PACK perforations from ft. to ft. SAND LAYER . perforations from _____ ft. to ____ ft. FROM 85FT TO 164FT perforations from _____ ft. to _____ (7) SCREENS: Well screen installed? | Yes | No SWABED IN Manufacturer's Name GRAVEL Diam. Slot size Set from .. ADD 90 MILLS PERF. Diam. Slot size Set from ft. to -ERATIONS IN 10" CASE --ING 95 N to 112 KX Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? ☐ Yes ☐ No If yes, by whom? gal./min. with ft. drawdown after hrs. Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. perature of water Depth artesian flow encountered 5/13 1976 Completed 5/25 Work started Date well drilling machine moved off of well (9) CONSTRUCTION: BENTONITE **Drilling Machine Operator's Certification:** Well seal-Material used This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal [Signed] W. Pankalla Date 7-7 , 1976 Number of sacks of cement used in well seal Drilling Machine Operator's License No.47/ Number of sacks of bentonite used in well seal Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name B	UD'S WELL DRILLING TWOLE TELEVER RIDGE RD.	
125	Principal of corporation ING	(Type or print)
AddressA	LBANY, OREGON 97327	
	a Jankell	W
	(Water Well Contract	ctor)

Contractor's License No. 621 Date 7-7, 1974

.125 lbs./100 gals.

Was a drive shoe used? Yes No Plugs Size: location ft.

Was well gravel packed? X Yes \(\subseteq \) No Size of gravel: \(\subseteq \subseteq \).

depth of strata

\$5 ft to 104

Did any strata contain unusable water?

Yes

No

Type of water?

Method of sealing strata off