STATE OF OREGON WATER WELL REPORT

RECEIVE

01943

APRILE 1985 PE or PRINT IN INK (as required by ORS 537.765) (for official use only) WATER RESOURCES DEPT (1) OWNER: (10) LOCATION OF WELL by legal description: SALEM, OREGON 5W 1/4 SW 1/4 of Section 47 Name WEYERHAEUSER CO Address PO BOX 235 (Township is North or South) Range_ (Range is East or West) **AURORA** State Orggon Lot Block (2) TYPE OF WORK (check): MAILING ADDRESS OF WELL (or nearest address) Reconditioning New Well Deepening \square Reconditioning 4 Same If abandonment, describe material and procedure in Item 12 (11) WATER LEVEL of COMPLETED WELL: (3) TYPE OF WELL:

Rotary Air
Cable Rig
Driven (4) PROPOSED USE (check): Domestic ☐ Municipal Depth at which water was first found Thermal: ft. below land surface. DateMar 11.1985 Static level Rotary Mud Dug ☐ Withdrawal ☐ Reinjection Irrigation Other: GRAVE FEED WELLS
Piezometric Grounding Test Artesian pressure lbs. per square inch. Date (12) WELL LOG: Diameter of well below casing (5) CASING INSTALLED: Steel Plastic Plastic Depth drilled ft. Depth of completed well N/A Threaded Formation: Describe color, texture, grain size and structure of materials; and show thickness ft. to ... 240 CLASS 160 and nature of each stratum and aquifer penetrated, with at least one entry for each change of ft. Gauge formation. Report each change in position of Static Water Level and indicate principal " Diam. from water-bearing strata. LINER INSTALLED: Steel Plastic MATERIAL. Threaded $\overline{\Box}$. From SILT BROWN 1 86 .ft. to ft. ... Gauge ... CEMENT GRAVEL 86 118 (6) PERFORATIONS: **CLAY GREY** 118 142 Size of perforations in. by in. CLAY TAN 142 150 perforations from CLAY GREEN 150 163 perforations from ft. to ft. SAND CLAY LAYERS 163 196 ft. to ft. CLAY GREEN 196 208 SAND (7) SCREENS: 208 212 Well screen installed?

Yes

No CLAY BLUE GREY 212 244 Manufacturer's Name CLAY LT BLUE 244 264 Туре SAND SILTY GREY Diam. Slot Size Set from ft. to ft. 264 278 SAND WOOD GRAVEL 27R 280 Slot Size Set from SILT SAND LAYERS 280 293 Drawdown is amount water level is lowered (8) WELL TESTS: below static level Was a pump test made?

Yes No If yes, by whom? ADDITIONAL INFORMATION ON RACK gal./min. with ft. drawdown after hrs. Air test gal./min. with drill stem at Bailer test gal./min. with ft. drawdown after hrs. Artesian flow note: Depth measured from top of well (ie, 1' perature of water Depth artesian flow encountered ... above oround level) Date work started Feb 06 Mar 11 85 /completed_ (9) CONSTRUCTION: Special standards: Yes ♥□ No □ Date well drilling machine moved off of well Mar 14 1985 Well seal—Material used BENTONITE. (unbonded) Water Well Constructor Certification (if applicable): Well sealed from land surface to25. This well was constructed under my direct supervision. Materials used and Diameter of well bore to bottom of seal in. information reported above are true to my best knowledge and belief. Diameter of well bore below seal in. Amount of sealing material [Signed] sacks 🛛 pounds 🗖 How was cement grout placed? 5ramilar Bentonite (bonded) Water Well Constructor Certification: SB34200 Issued by: Thomas Haun (Surety Company Name) On behalf of BECK WELL DRILLING
(type or print name of Water Well Constructor) Depth 240 Turbine HP 100 Was pump installed? ... Was a drive shoe used? Tyes I No Plugs Size: location Did any strata contain unusable water?

Yes No This well was drilled under my jurisdiction and this report is true to the Type of Water? best of my knowledge and belief: depth of strata Method of sealing strata off (Signed) ... Size of gravel: 1/4 MIDUS Was well gravel packed? Yes □ No Gravel placed from