NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CLAC

STATE OF OREGON

(Please type or print) (Do not write above this line)

State Well No.

01979 State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	•
Name Jim Seymore	County Clackamas Driller's well numb	er123 -
Address Rt.1 Box 107	SW 34 SW 34 Section 36 T.4S R.	1W .w.n
Hubbard, Or, 97032	Bearing and distance from section or subdivision	
(2) TYPE OF WORK (check):		-
New Well 🔀 Deepening 🗌 Reconditioning 🗎 Abandon 🗀	ü	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	140 f
Rotary X Driven D Domestic X Industrial Municipal D	17.4	
Cable	11. Delow faild Suries	ace. Date $7-26-79$
	Artesian pressure lbs. per square in	ch. Date
CASING INSTALLED: Threaded □ Welded X	(12) WELL LOG: Diameter of well below	w casing 6"
6 "Diam from 0 ft to 140 ft Gage • 250	Diameter of went belov	4 = 0
"Diam. from		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and and show thickness and nature of each stratum a	structure of materials
DEDECDATIONS	with at least one entry for each change of formation.	Report each change i
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principa	I water-bearing strats
Type of perforator used	MATERIAL	rom To SWL
Size of perforations in. by in.	_Top soil	0 2
perforations fromft. toft.	Clay, brown	2 18
perforations fromft. toft.	Clay, blue	18 78
perforations from ft. to ft.		78 88
(7) SCREENS: Well screen installed? Ver Ver		88 9.7
Well screen mistation Tea X No		97 104
Manufacturer's Name TypeModel No	Sand, clay, black, fine, bl.10	
Diam. Slot size Set from ft. to ft.	* Sandstone, soft, fract. 14	40 150
Diam. Slot size Set from ft. to ft.	*,	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? X Yes No If yes, by whom?driller	JUL 3 1 1979	
Yield: 20 gal./min. with 11 ft. drawdown after 3 hrs.	WATER RESOURCES DEPT	
gar,/min. with II it. drawdown after O hrs.	WATER RESOURCES DELL	
The state of the s	SALEM, OREGON	
(H) H H H H H H H H H H H H H H H H H H	The state of the s	
Bailer test gal./min. with ft. drawdown after hrs.	-	
Artesian flow g.p.m.		<u> </u>
perature of water Depth artesian flow encountered ft.	Work started 7-25 1979 Completed	7-26 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-26 179
Comont	v-	
TARREST TARREST TO THE STATE OF	Drilling Machine Operator's Certification: This well was constructed under my dir	
Well sealed from land surface toft. Diameter of well bore to bottom of seal10in.	Materials used and information reported abo	ect supervision. ve are true to my
Diameter of well bore below seal	best knowledge and belief.	
Yumban ad 13	[Signed] Model Manuary Date	, 7 <u>-27</u> , ₁₉ 79
Sacks of cement used in well seal sacks How was cement grout placed? Pressure grouted from	Drilling Machine Operator's License No.	837
24 ft. to land surface.	The state of the s	
	Water Well Contractor's Certification:	. •
	This well was drilled under my jurisdiction	and this report is
Was a drive shoe used? 🗷 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable_water? 🛽 Yes 🔏 No	Name B & G Drilling (Person, firm or corporation)	/M
'ype of water? depth of strata	Address 10030 S. Macksburg Rd	(Type or print)
Method of sealing strata off	V, V / / / / * ` .	IL OF
	[Signed] Alorge & Warnery	7
Vas well gravel packed? ☐ Yes No She of gravel:	(Water Well Confractor)	
Fravel placed from ft. to ft.	Contractor's License No. 637 Date	7-27 , ₁₉ 79