12(5000	4/IW-36 R(1)
ORIGINAL NOV 16 1956 WATER WELL DRILL	ERS REPORT   Do Not State Well No
Duplicate with the STATE ENGINEER STATE OF OR SALEM, OREGON STATE ENGINEER	
(1) OWNER: SALEM, OREGON	
(1) OWNER: SALEM, ORDER	(10) WELL TESTS:
Name Okali	Was a pump test made?   ☑ Yes □ No If yes, by whom? Driller
Address Rt 1 Box 222 020	dela: 540/ gal./min. with ft. draw down after hrs.
Hubbard Ore.	/" 160
(2) LOCATION OF WELL:	T#A 00
D 3 A	Artesian flow g.p.m.  Shut-in pressure lbs. per square inch.
R. F. D. or Street No. RT 1 Box 222	Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivision corner	Temperature of water 53 Was a chemical analysis made? ☐ Yes ☐ No
Fart of the south half of the South-	Was electric log made of well? ☐ Yes ☐ No
east quarter of Section 36. T. 45. R.	(11) WELL LOC:
1 W., of the W. N. in the County of Clackenes and State of Oregon described	(11) WELL LOG:
Glackers and State of Oregon described (3) TYPE OF WORK (check):	Diameter of well,
New well   Deepening   Reconditioning   Abandon    Abandon    ■	Total depth 2200 15 Depth of the party of th
abandonment, describe material and procedure in Item 11.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:	O ft. to 5 ft. Top soil
Domestic M Industrial Municipal Rotary	5 " 55 "Light brown silt
Cable 4	55 " 70 "Blue silt
Irrigation ☐ Test Well ☐ Other ☐ Dug Well ☐	70 "81 "Blue clay & silt mixed
CASING INSTALLED: If gravel packed	81 " 83 . "Cement gravel
Threaded   Welded 4	83 " 109 "Dark brown wilt & fine black
Gage or Diameter from to FROM ft. to ft. Diam. Wall of Bore ft. ft.	" sand mixed
FROM ft. to ft. Diam. Wall of Bore it. It.  "Top to bottom" "	TOO THE DELICE
n n n	123 " 127
11 11 11 11 11 11	" " " "
11 21 21 21 21	11 12
" " " " " " " " " " " " " " " " " " "	n n
1, pc and 5120 01 5100 01 11 mr 7 7	., .,
Describe joint Butt Weld	17 17
(7) PERFORATIONS:	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,
Type of perforator used Starr  in, length, by 15 in.	n n
SIZE of perforations in., length, by 15 in. FROM 126tt. to 129 ft. 5 perf per foot 4 No. of rows	37 37
" " " " " " " " " " " " " " " " " " "	1) ))
11 11 11 11 11 11 11 11 11	" "
n n n n n n n n n n n n n n n n n n n	11 17
n n n	21 29
SCREENS:	11 11
Give Manufacturer's Name, Model No. and Size	19 12
	n n
(8) CONSTRUCTION:	" "
Was a surface sanitary seal provided? ☐ Yes ☐ No To what depth ft.  Were any strata sealed against pollution? ☐ Yes ☐ No	Ground elevation at well site
If yes, note depth of strata	Work started Oct. 18 1856, Completed Oct. 26 1956
FROM ft. to ft.	Well Driller's Statement:
11 11 11 11 11 11 11 11 11 11 11 11 11	This well was drilled under my jurisdiction and this report is
METHOD OF SEALING	true to the best of my knowledge and belief.
(9) WATER LEVELS:	NAME John W. Beck Well Drilling
Depth at which water was first found 18 ft.	(Person, firm, or corporation) (Typed or printed)
Standing level before perforating bottom sealed ft.	Address Rt. 3, Box 45, Canby, Ore.
Standing level after perforating 60 ft.	Driller's well number \$5 /3/1/ 378
Log Accepted by:	[Signed] John W Beck
01. 11. 10. 10. 11. 11. 11. 11. 10. 10.	(Well Driller)
[Signed] Owner Owner	License No. 95 Dated Oct. 27 , 1956