

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED WATER WELL REPORT
STATE OF OREGON

JUN 25 1980 (Please type or print)
(Do not write above this line)

CLAC State Well No. 5s/1w-1cc
02012 State Permit No. _____

WATER RESOURCES DEPT

(1) OWNER: SALEM, OREGON

Name Jack R. Bigel
Address Rt 1 Box 246 F
Hubbard Ore.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

8" Diam. from 0 ft. to 15.5 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Johnson
Type Stainless Model No.
Diam. 7 1/2 Slot size .015 Set from 140 ft. to 150 ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? Yes No If yes, by whom? Driller
Flow: 170 gal./min. with 64 ft. drawdown after 6 hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 26 ft.
Diameter of well bore to bottom of seal 12 1/2 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed? Pumped

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number
SW 1/4 SW 1/4 Section 1 T. 5 R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 118 ft.
Static level 63 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8

Depth drilled 155 ft. Depth of completed well 150 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay	2	27	
Blue Clay	27	29	
Brown Clay	29	65	
Blue Clay	65	78	
Brown Sandy Clay	78	98	
Blue Clay	98	102	
Dark Blue Clay	102	108	
Light Blue Clay	108	112	
Dark Blue silty clay	112	118	
Dark sand	118	122	
Dark green clay	122	155	
Pipe was pulled back to 141 ft to uncover screens.			

Work started 5-23 1980 Completed 6-6 1980
Date well drilling machine moved off of well 6-7 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] John W. Beck Date 6-7, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 437

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Sw Beck well drilling
(Person, firm or corporation) (Type or print)

Address 24177 S. Skyline Dr. Canby Ore.

[Signed] John W. Beck
(Water Well Contractor)

Contractor's License No. 449 Date 6-7, 1980