

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

RECEIVED

CLAG
02051

STATE OF OREGON

(Please type or print)

NOV 2 1981

State Well No.

55/100-11 dd

State DEPT No.

WATER RESOURCES DEPT

SALEM, OREGON

(1) OWNER:

Name Gene Coronado
Address 4761 Killings Loop
Woodburn, Oregon 97071

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

6" Diam. from 0 ft. to 80 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Well: 35 gal./min. with 75 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement
Well sealed from land surface to 20 ft. ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 9 sacks
How was cement grout placed? grout pump
from bottom up outside
casing
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County CLATSOP Driller's well number
SE 1/4 SE 1/4 Section 11 T. 55 R. 1 W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level 40 ft. below land surface. Date 10-26-81
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 82 ft. Depth of completed well 80 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	12	
Grey Brown Clay	12	20	
Sandy clay Brown	20	30	
Blue clay Sticky	30	40	
COURSE BROWN SAND	40	75	
Med. Gravel	75	82	40

Work started 10-16 19 81 Completed 10-26 19 81
Date well drilling machine moved off of well 10-27 19 81

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] E. W. Sluice Date 10-30, 19 81
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1456

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name American Drilling Co. Inc.
(Person, firm or corporation) (Type or print)

Address P.O. Box 113, Hubbard, Ore.

[Signed] E. W. Sluice
(Water Well Contractor)

Contractor's License No. 779 Date 10-30, 19 81