## WATER WELL REPORT STATE OF OREGON

RECEIVED State Well
AUG 2 0 1982 State Perm

CLAC MUGUIJOL Stat

State Well No	55/IW	-13 ra
State Permit No.		

( 02003	SALEM, ORECCH		
(1) OWNER:	(10) LOCATION OF WELL:		
Name STEVE SCHNFIDER	County Clackamas Driller's well n	umban	
Address 33085 SOUTH MERIDIAN ROAD	NE NE	R. 1W W.M.	
City WOODBURN State OREGON	Tax Lot # Lot Blk	Subdivision	
(2) TYPE OF WORK (check):	Address at well location:		
٧٧			
	(11) WATER LEVEL: Completed we	]]	
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found	50 ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		0.40.400	
Rotary Air XX Driven		square inch. Date 8/2/82	
Rotary Mud  Dug		OII	
The state of the s	(12) WELL LOG: Diameter of well below can be perfectly drilled 156 ft. Depth of co	ising	
5) CASING INSTALLED: Steel XX Plastic D			
Threaded $\square$ Welded XX 8" Diam. from $+4$ ft. to $156$ ft. Gauge $250$	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry		
	for each change of formation. Report each change in po- and indicate principal water-bearing strata.	sition of Static Water Level	
LINER INSTALLED:			
	MATERIAL	From To SWL	
" Diam. from ft. to ft. Gauge	TOP SOIL	0 2	
(6) PERFORATIONS: Perforated? (X) Yes $\square$ No	CLAY_BROWN	2 16	
Type of perforator used Mills Knife	CLAY GRAY	16 20	
Size of perforations $\frac{1}{4}$ in. by $\frac{1}{4}$ in.	CLAY_SAND_BROWN	20 50	
300 perforations from 112 ft. to 126 ft.	SANDSTONE BROWN	50 56	
	CLAY_SAND_BROWN	56 68	
perforations from ft. to ft.	GRAVEL-SAND BROWN	68 88	
(7) SCREENS: Well screen installed?   Yes M No	SANDSTONE BROWN	88 90	
Manufacturer's Name	- CLAY BROWN	90 94	
Type Model No.	CLAY GRAY SAND BLACK	94 112	
Diam. Slot Size Set from ft. to ft.	THE PERSON NAMED IN COLUMN 1	12 126 50 126 128	
Diam. Slot Size Set from ft. to ft.		28 142	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		42 156	
below static level		-12 130	
Wes a pump test made? ☐ Yes ☐ No If yes, by whom?			
id: gal./min. with ft. drawdown after hrs.			
Air test 180 gal./min. with drill stem at 150 ft. 10 hrs.			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
hperature of water Depth artesian flow encountered ft.	Work started 7/28 1982 Completed	8/2 19 82	
(9) CONSTRUCTION: Special standards: Yes □ No 🕅	Date well drilling machine moved off of well	8/2 19 82	
Well seal—Material used Cement	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct sup and information reported above the true to in these	pervision. Materials used	
Diameter of well bore to bottom of seal12 in.	and information reported above she true to in the	t knowledge and belief.	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date8/.11., 1982	
Number of sacks of cement used in well seal	Drilling Machine Operator's License No 1038	}	
How was cement grout placed? Pressure grouted			
	Water Well Contractor's Certification:	3.41	
Was pump installed?	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
V	NameBARNETT DRILLING & PUMPSINC		
Was a drive shoe used?			
Type of Water? depth of strata	Address157,50SOUTHWROLSTADDH	(LKE,UKE,LLLLY,0)	
Method of sealing strata off	[Signed] Sary W. Oor	red	
Was well gravel packed? ☐ Yes XXNo Size of gravel:	(Water Well Contractor		
Gravel placed from	Contractor's License No7.6.4Date8./.11	, 198.2	