

The original and first copy of this report are to be filed with the

STATE OF OREGON WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON

within 30 days from the date of well completion.

RECEIVED SEP 21 1970 STATE ENGINEER SALEM, OREGON

(Please type or print)

(Do not write above this line)

CLAC 02120

State Well No. 2/1W-13

State Permit No.

14aa 2/1W-13

(1) OWNER:

Name: Andrey Kaya
Address: Ph #1, Box #29, Hubbard, Or. 97032

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [X]
Diam. from 0 ft. to 150 ft. Gage 2.50

(6) PERFORATIONS:

Perforated? [X] Yes [] No
Type of perforator used: Mills
Size of perforations: 3/8 in. by 2 in.
300 perforations from 110 ft. to 135 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name:
Type: Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? Stettin
Yield: 200 gal./min. with 44 ft. drawdown after 1 hrs.

CONSTRUCTION:

Well seal-Material used: Puddle Clay
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 8 1/2 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal:
Number of sacks of bentonite used in well seal:
Brand name of bentonite:
Number of pounds of bentonite per 100 gallons of water:
Was a drive shoe used? [X] Yes [] No Plugs: Size: location: ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County: Clatsop Driller's well number:
1/4 1/4 Section 13+14. 58 R. 1 West. W.M.
Bearing and distance from section or subdivision corner:

(11) WATER LEVEL: Completed well.

Depth at which water was first found: 45 ft.
Static level: 50 ft. below land surface. Date: 9/15/70
Artesian pressure: lbs. per square inch. Date:

(12) WELL LOG:

Diameter of well below casing: 8"
Depth drilled: 160 ft. Depth of completed well: 160 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Top Soil (0-5), Brown Clay (5-33), Brown Sand (33-45), Brown Clay (45-70), Brown Sand (70-80), Brown Clay (80-98), Brown Sand (98-108), Gravel, tight (108-135), Grey Clay (135-152), Brown Sand (152-156), Brown Clay (156-160).

Work started: 9/10 1970 Completed: 9/18 1970
Date well drilling machine moved off of well: 9/15 1970

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] J. J. Terrell Date: 9/18 1970
(Drilling Machine Operator)
Drilling Machine Operator's License No. 179

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name: J. F. Terrell Well Drilling
Address: 8425 Wheatland Rd. No. Salem, Ore.
[Signed] Mrs. Joan B. Terrell
(Water Well Contractor)
Contractor's License No. 460 Date: 9/18 1970