NOTICE TO WATER WELL CONTRACTOR
The original and first copy (1) (1)
of this report are to be
filed with the

Vern C. Johnson

Rt 2, Woodburn, Oreg.

(1) OWNER:

Name

Address

19 WATER WELL REPORT

CLAC)	· · · · · · · · · · · · · · · · · · ·
02155	•
State Well No	5/1W-14 M

THE WITH THE	Martin M. V. and L. A. M. S. States States States
STATE ENGINEER, SALEM, OREGON 97310	ENDINISTATE OF OREGON
within 30 days from the date of well completion.	(Please type or print)

11) WELL TESTS: Drawdown is amount lowered below static le	water lev	el is
Was a pump test made? $\bigcirc$ Yes $\square$ No If yes, by who		ller
rield:160 gal./min. with 70 ft. drawdov		hr
, 17 ,		<del>"</del>
<i>n</i>		"
Bailer test gal./min. with ft. drawd	own after	hr
Artesian flow g.p.m. Date		
Temperature of water Was a chemical analysis	made? 🔲	Yes 🙀 N
(12) WELL LOG: Diameter of well below or	ising8	
Depth drilled 218 ft. Depth of completed we	<sub>11</sub> 170	f
	ıl and stru	icture, an
Formation: Describe by color, character, size of materic how thickness of aquifers and the kind and nature of tratum penetrated, with at least one entry for each of	the mater hange of	formatio
MATERIAL	FROM	то
		,
Top soil brn. Clay brn.	7	12
•	*~	10
Clay sandy brn. Sand fine brn.	12	E0
	40	70
Clay sandy brn.	<del>  58</del>	05
Med conglomerate tight	+ <del>05</del>	85
Sand fine brn.	<del>  85  </del>	93
Clay & mixed gravel brn.	93	103
Med conglom brn.	103	<del>134</del>
Looser gravel grey	134	<del>136</del> —
Med conglom. grey	136	<del>138</del> –
Clay grey	138	<del>170</del> —
Soft claystone grey , cavy	170	<del>218 -</del>
	1	-
*		-
later coming fromgravel	<del> 103  </del>	<del>138 -</del>
· · · · · · · · · · · · · · · · · · ·	<del>                                     </del>	-
lole caved back to 170 ft.	<del>                                     </del>	<del> </del>
	<del> </del>	1
, 1/2	1	
	<del>                                     </del>	<del> </del>
	+	<del> </del>
1,000		
Work started 6/13 1966 Completed 7	<del>/</del>	6
7/).	•	19
Date well drilling machine moved off of well		19
(13) PUMP:		
Manufacturer's Name Jacuzzl		
		•••••
Turbine	T D / 17	
Type: Turbine	H.P&V	

(2) LOCATION OF WELL:	" " "		
County ( ) a ckama s Driller's well number	Bailer test gal./min. with ft. drawdown after		
County Clackamas Driller's well number  14 1/4 Section T. R. W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made?   Y		
1450ft N& 1000 ft E of SW cor ofsec	(12) WELL LOG: Diameter of well below of	easing8	
14 T.5 S. R 1 W. of W.M.	Depth drilled 218 ft. Depth of completed w	<sub>vell</sub> 170	
	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	the materia change of f	
	MATERIAL	FROM	
(3) TYPE OF WORK (check):		<del>-ii</del>	
New Well	Top soil brn.	10	
andonment, describe material and procedure in Item 12.	Clay brn.	<del>     </del>	
(4) PRODUCED LICE (-1L). (5) WYDE OF YOUR	Clay sandy brn.	12	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sand fine brn.	40	
Cable X Jetted	Clay sandy brn.	58	
Irrigation Test Well Other Dug Bored	Sand fine brn.	65 85	
(6) CASING INSTALLED: Threaded Welded	Clay & mixed gravel brn.	93 1	
	Med conglom brn.	103 1	
	Looser gravel grey	134	
	Med conglom. grey	136 I	
	Clay grey	138 1	
MITS MILLS	Soft claystone grey , cavy	170 2	
Type of perforator used		+ +	
Size of perforations 4 in. by 160 in.  504 perforations from 103-160 ft. to ft.	A PROPERTY AND A STATE OF THE	+ +	
perforations from	Water coming fromgravel	+103 1	
perforations from ft. to ft.		+ +	
perforations fromft. toft.	Hole caved back to 170 ft.	+ +	
perforations fromft, toft.			
(8) SCREENS: Well screen installed? ☐ Yes ▼ No			
Manufacturer's Name			
Model No			
Slot size Set from ft. to ft.	Work started 6/13 1966 Completed	7/4	
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well	+	
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in sealBentonite&cuttings.			
Depth of seal ft. Was a packer used?	Manufacturer's Name Jacuzzl Type: Turbine	н.р. 20	
Diameter of well bore to bottom of seal	Type: Luroine	H.P	
Were any loose strata cemented off?   Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? ▼ Yes □ No	This well was drilled under my jurisdiction	and this	
Was well gravel packed? ☐ Yes ☆ No Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to ft.	NAMED Stadali & Sons	*	
Did any strata contain unusable water?   Yes  No	NAMER. Stadeli & Sons Rt 3 Box 169, Silverton, Oregonical		
Type of water? depth of strata	Rt 3 Box 169,511verton,		
Method of sealing strata off	Drilling Machine Operator's License No.	<b>3</b> 4	
(10) WATER LEVELS:	Drilling Machine Operator's License No.		
Static level 60 ft. below land surface Date 7/4/66	[Signed] Jan J. Stallic (Water Well Contractor)	 }	
Artesian pressure lbs. per square inch Date	Contractor's License No. 296 Date7/1.		
	Contractor's License No Date	·J	

Drilling Machine Operator's License No. 84	
[Signed] Jaul & Stadeli	
(Water Well Contractor)	
Contractor's License No. 296 Date7/15	, 1966