## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

TER WELL REPORT STATE OF OREGON

STATE OF STA		7770-1	
(1) OWNER:	(11) LOCATION OF WELL:		
Name GENEKAL FOODS CORP. BIRDS EYE DIV	County CLACK. Driller's well num	nber 53/5	
Address WOOOBURN ORE.	SW 1/2 SW 1/2 Section 17 T. 53		
	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):	:		
New Well   Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well be	low casing	
Rotary   Driven   Domestic   Industrial Municipal	Depth drilled 335 ft. Depth of completed well 235 ft.		
Dug	Formation: Describe color, texture, grain size an	<del></del>	
CASING INSTALLED: Threaded   Welded   W	and show thickness and nature of each stratum with at least one entry for each change of forma in position of Static Water Level as drilling proc	and aquifer penetrated, tion. Report each change	
	MATERIAL		
	TOP SOIL	From To SWL	
A DEDUCATION A MILES OF THE PROPERTY OF THE PR	CLAY AND SILT	227	
Tellorated A les [] No.		77 40	
ype of perforator used	GREY SILT AND SAND	40 91	
Size of perforations 2/8 in. by 1/4 in.	STICKY GARRY CLAY	91 94	
600 perforations from 192 ft. to 202 ft.	SAND AND SILT	94121	
840 perforations from 2/7 ft. to 226 ft.	GRAVEL AND SAND	121 132	
perforations from ft. to ft.	CLAY AND SAND	132 155	
perforations from	GRAVEL	155 156	
perforations from ft. to ft.	SILT AND SAND	156 191	
(7) SCREENS: Well screen installed?   Yes No	SAND AND GRAVEL	191 201	
Manufacturer's Name	GRAVEL SILT CLAY	201 210	
Type Model No.	GRAVELAND CLAY	2/0 2/2	
Diam. Slot size Set from the ft. to ft.	SAND AND GRAVEL	2/3 732	
Diam. Slot size Set from ft. to ft.	BROWN CLAF	037-243	
(8) WATER LEVEL: Completed well.	BROWN AND GREY CLAY	24/2 355	
Static level 53 ft. below land surface Date 7/11/69			
sian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? Yes No If yes, by whom? STRASSER Weld: 890 gal./min. with 97 ft. drawdown after 8 hrs.	Work started MAY 6 1969 Completed	JULY 17 1969	
geld: 840 gal./min. with 47 ft. drawdown after 8 hrs.	Date well drilling machine moved off of well	10LY 18 1969	
" " " "	Dulling Machine Organization of the transfer	7027 28 307	
Della de d	Drilling Machine Operator's Certification:  This well was constructed under my direction.	ect supervision. Mate-	
	rials used and information reported above knowledge and belief	are true to my best	
Artesian flow g.p.m. Date	Alan Nah	7/2, 60	
Temperature of water 54 Was a chemical analysis made? ☐ Yes No	[Signed] (Drilling Machine Operator)	ate, 1907	
(10) CONSTRUCTION:	Drilling Machine Operator's License No		
Well seal—Material used			
Depth of sealft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes \( \sum \) No	NAME RISTRASSER DRILLING CO		
Did any strata contain unusable water?  Yes No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 8/105E SUNSETLAND	FORTLAND ORE	
	DILY		
Method of sealing strata off	[Signed] Lolen d. Mas	sev	
Was well gravel packed?  Yes No Size of gravel:	(Water Well Contractor	7/2 103	
Gravel placed from ft. to ft.	Contractor's License No Date	1 1969	