Size of gravel:

Gravel placed from

Was well gravel packed?

Yes Wo

STATE ENGINEER, SALEM, OREGON 97310 CPlease type	RECEIVEU L REPORT OREGON FEB 1 9 1975 or print) STATE ENGINEER ove this HeDALEM, OREGON State Permit No.	
(1) OWNER:	(10) LOCATION OF WELL:	_
Name Anton J Pirkl	County Clackamas Driller's well number 93-74	
Address 1603 Box 206	34 34 Section 1 T. 5S R. 1E W.	
Molalla, Oregon		Wa.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well □ Deepening 🖽 X Reconditioning □ Abandon □		_
If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 81 Static level 45 ft. below land surface. Date 11-8-	ft.
Rotary XX Driven Domestic XXIndustrial Municipal Domestic XXIndustrial Municipal	Static level 45 ft. below land surface. Date 11-8-	-'/ <i>1</i>
Dug	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welder 15. "Diam. from 73. ft. to 93. ft. Gage 188. "Diam. from ft. to ft. Gage 7. Diam. from ft. Gage 7. Diam. ft. Diam. ft. Gage 7. Diam. ft. Diam. ft. Gage 7. Diam. ft. Gage 7	(12) WELL LOG: Diameter of well below casing	ft. ls; ed,
Type of perforator usedTorch .:	MATERIAL From To SWL	_
Size of perforations 1/8 In by 12	Cemented gravel 81 94 45	
6 perforations from 78 ft. to 92 ft.	Grey Clay 94 96	<u></u>
perforations fromft. toft.		
perforations fromft. toft.	••	
(7) SCREENS: Well screen installed? □ Yes ☒Xo Manufacturer's Name Model No. Type Model No. Diam. Slot size Set from ft. to Diam. Slot size Set from ft. to ft. ft.		_ _ _ _
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		_
was a pump test made? XXes □ No If xes, by whom? driller yield: 60 gal./min. with 40 ft. drawdown after 1 hrs. """ """		_ _ _
" " "		_
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		—
perature of water Depth artesian flow encountered ft.	W	
Depart are state 110W encountered	Work started 11-8 19 7/Completed 11-8 19 7	
(9) CONSTRUCTION: No Change	Date well drilling machine moved off of well 11-8 197	4
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my direct supervisio	
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to n best knowledge and belief.	цу
Diameter of well bore below sealin.	[Signed] fuger M. Spylls Sate 12-3, 19.	74
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 271	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	
Brand name of bentonite	W. L. W. I. C L. C. L.	_
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	_
of water	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	is
Was a drive shoe used? ☐ Yes ☐ XX Plugs Size: location ft.	Claurian Dadilidan and Committee	
Did any strata contain unusable water? 🗆 Yes 🖔 🛪 o	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 1109 Molalla Avenue, Oregon City	<u> </u>
Method of sealing strata off		
Was well gravel nacked? Ves KWo Size of gravel	[Signed] (Water Well Contractor)	