WATER WELL REPORT
STATE OF OREGON

CLAC
02261

RECEIVED
AUG 6 1981
WATER RESOURCES DEPT
SALEM, OREGON

State Well No. 5S/1E-4

State Permit No.

(1) OWNER:

Name DeWayne Beckner
Address 307751 S.E. Arow Ct.
City Canby State Or 97013

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air ☒ Driven ☐
Rotary Mud ☐ Dug ☐
[redacted] ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

[redacted] CASING INSTALLED:

Steel ☒ Plastic ☐
Threaded ☐ Welded ☒

6 " Diam. from +1 ft. to 76 ft. Gauge .250
" Diam. from ft. to ft. Gauge

[redacted]INER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
[redacted] gal./min. with ft. drawdown after hrs.
" " " "
Air test 30 gal./min. with drill stem at 76 ft. 1.5 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
[redacted]sian flow g.p.m.
[redacted]erature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒
Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 6 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 5 sacks
How was cement grout placed? grout pump & trimmie pipe

Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number D-367-881
¼ ¼ Section 4 T. 5S R. 1E W.M.
Tax Lot # Lot Blk Subdivision
Address at well location:

(11) WATER LEVEL: Completed well.

Depth at which water was first found 23 ft.
Static level 18 ft. below land surface. Date 8/4/81
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 76 ft. Depth of completed well 76 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
brown soil	0	24	
gray clay	24	36	
brown sandy clay	36	50	
light gray clay	50	68	
1" minus gravel,water	68	76	

Work started 8/3 1981 Completed 8/4 1981
Date well drilling machine moved off of well 8/4 1981

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Pat Wallace (Drilling Machine Operator) Date 8/5, 1981
Drilling Machine Operator's License No. 887

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name S & M Drilling & Supply, Inc. (Person, firm or corporation) (Type or print)
Address 399 S.E. Walnut St., Canby, Oregon 97013
[Signed] (Water Well Contractor)
Contractor's License No. 497 Date 8/5, 1981

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690