NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

7-2

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

CLAC 02262

State Well No. 55/1E-4 aa
State Permit No.

(1) OWNER:
Name Conrad Quist
Address 9000 S. Barnard Rd
Canby, Ore ph 651-2343

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☑
8" Diam. from 0 ft. to 324 ft. Gage 1250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used STAR
Size of perforations 1 1/4 in. by 3/8 in.
1835 perforations from 60 ft. to 320 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Driller
Yield: 600 gal./min. with 65 ft. drawdown after 6 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 51 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 26 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 36 sacks
How was cement grout placed? Pump
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number
NE ¼ NE ¼ Section 4 T. 5S R. 1E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 1 ft.
Static level 51 ft. below land surface. Date Aug 11
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 348 ft. Depth of completed well ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Silt Brown	2	13	
Sand Fine Brown	13	18	
Silt Brown	18	21	
Clay Silty Brown	21	29	
Clay Blue	29	36	
Cement Gravel Brown	36	93	51
Cement Gravel Blue	93	133	
Clay Blue	133	153	
Sandstone	153	156	51
Clay Blue	156	184	
Sand	184	187	
Clay Blue	187	262	
Sandstone	262	264	51
Claystone, Blue Green	264	305	
Silty Clay	305	314	
Sandstone	314	322	51
Clay Blue	322	348	

RECEIVED SEP 5 1979 WATER RESOURCES DEPT. SALEM, OREGON

Work started July 7 1979 Completed Aug 11 1979
Date well drilling machine moved off of well Aug 11 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Richard J Beck (Drilling Machine Operator) Date Aug 11, 1979
Drilling Machine Operator's License No. 1200

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name J W Beck Weildrilling (Person, firm or corporation) (Type or print)
Address 24437 S Skyline Dr Canby Ore
[Signed] John W Beck (Water Well Contractor)
Contractor's License No. 449 Date 17 Aug 13, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP 456-119