NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

RECEIVED
AUG 5 1977

(Do not write above this line)

CLAC 02394 CLAC

State Well No. 5S/1E-8

State Permit No.

(1) OWNER:
WATER RESOURCES DEPT, SALEM, OREGON

Name Virginia Canoilov

Address 31372 S. Mulkey Rd. Canby, Oregon 97013

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☒

6" Diam. from 110 ft. to 194 ft. Gage 250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Miller

Yield: 100 gal./min. with 30 ft. drawdown after 2 hrs.

" " "

" " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Unk. Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used

Well sealed from land surface to ft.

Diameter of well bore to bottom of seal in.

Diameter of well bore below seal in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons of water lbs./100 gals.

Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number

¼ ¼ Section 8 T. 5S R. 1E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 210 ft.

Static level 70 ft. below land surface. Date 7-15-77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing

Depth drilled 225 ft. Depth of completed well 225 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Sand & gravel grey	188	163	70
Clay grey (gritty)	163	165	
Clay brown (gritty)	165	180	
Clay grey	180	210	
Sand black W.B.	210	225	70

Work started 7-13 19 77 Completed 7-15 1977

Date well drilling machine moved off of well 7-16 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Robert Stutes (Drilling Machine Operator) Date 7-29, 1977

Drilling Machine Operator's License No. 776

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name [illegible] (Person, firm or corporation) (Type or print)

Address 22290 S. Ireland Rd. Canby, Oregon

[Signed] [illegible] (Water Well Contractor)

Contractor's License No. 537 Date July 29, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119