

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON

within 30 days from the date of well completion.

RECEIVED
AUG 6 1968

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

Do not write above this line)

SALEM OREGON

State Well No.

5/1-15

State Permit No.

02514

6-6565

(1) OWNER:

Name Harold ConklinAddress Town House Apt #13 Canby, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒

8" Diam. from 0 ft. to 130 ft. Gage 1/4"

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in. by	in.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 85 ft. below land surface Date 8/1/68

Man pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? driller

ld: 60 gal./min. with 38 ft. drawdown after 3 hrs.

" " " "

" " " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water Was a chemical analysis made? ☐ Yes ☒ No

(10) CONSTRUCTION:

Well seal—Material used Puddled mud

Depth of seal 25 ft.

Diameter of well bore to bottom of seal 12 in.

Were any loose strata cemented off? ☐ Yes ☒ No DepthWas a drive shoe used? ☐ Yes ☒ NoDid any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Clackamas Driller's well number

1/4 1/4 Section 15 T. 5S R. 1E W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 8

Depth drilled 140 ft. Depth of completed well 140 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Brown top soil	0	1	
Brown sandy clay	1	19	
Blue clay	19	23	
Brown clay & fine gravel	23	29	
Cement gravel	29	41	
Hard brown clay	41	47	
Brown sandy clay	47	57	
Brown clay & gravel	57	65	
Brown clay w/blue streaks	65	101	
Purple clay, sandy (water bearing)	101	107	
Black clay	107	124	
Blue clay	124	132	
Hard black sandstone	132	135	
Black sand & blue clay striped	135	140	

Work started July 25 1968 Completed August 1 1968

Date well drilling machine moved off of well August 1 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William D. Christensen Jr. Date Aug 2, 1968.
(Drilling Machine Operator)

Drilling Machine Operator's License No. 500

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller
(Person, firm or corporation) (Type or print)

Address P.O. Box 342 Hubbard, Oregon

[Signed] John T. Miller
(Water Well Contractor)

Contractor's License No. 277 Date August 2, 1968.