NOTICE TO WATER WELL CONTRACTOR

The original and first dolly MAY 13 1966 WATER WELL REPORT filed with the STATE ENGINEER, SALEMSTEROF EXIL NGINEER TATE OF OREGON 6 570

State Well No. 5/1-15 A

within 30 days from the date of well completion. SALEM OREGON (Please types)	pe or print) G-3586 State Permit No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount to lowered below static le	water level	l is
Name David Schriever	Was a pump test made? Yes \(\bar{\text{No}}\) No. If yes, by whom		
Address Rt. 3, Box 275	Yield: 223 gal./min. with 50 ft. drawdow		hrs.
Molalla, Oregon	<u>" 250 " 55 "</u>	3	3 "
(2) LOCATION OF WELL:	" " " "		"
	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Clackamas Driller's well number	Artesian flow g.p.m. Date		
<u>SW 4 SW 4 Section 15 T. 5S R. 1E W.M.</u>	Temperature of water 54 Was a chemical analysis r	made? 🔲 Y	es 🔀 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing	8
	l`´	7 ~0	(
	Depth drilled 158 ft. Depth of completed we		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of a stratum penetrated, with at least one entry for each continuous	t and structhe materic	il in each
(a) Myde of Work (.L.,.L)	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Top soil	0	2
Well	Clay, brown	2	9
abandonment, describe material and procedure in Item 12.	Clay, brown, soft silty	9	17
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Clay, blue	17	22
Rotary □ Driven □	Cemented gravel	22	31
Domestic ☐ Industrial ☐ Municipal ☐ Cable ☐ Jetted ☐ Irrigation ※ Test Well ☐ Other ☐ Cable ☐ Jetted ☐	Clay, brown	31	35
Dug Bored	Clay, tan, soft	35	39
(6) CASING INSTALLED: Threaded Welded	Clay, tan, sandy	39	43
35/8 "Diam. from + 1 ft. to 1481/2 ft. Gage .250	Clay, tan, sticky	43	79
	Clay, purple	79	85
	Sand, brown (,15 gal. min.)	85	88
/// DEDEODATIONS.	Clay, blue, sandy	88	.91
(7) PERFORATIONS: Perforated? ☐ Yes ☐ No	Clay, blue	91	100
Type of perforator used	Clay, blue, sandy	100	102
Size of perforations in. by in.	Sand, black, fine (24 gal.	102	106
perforations from ft. to ft.	min. with 85 ft. strata)	-04	
perforations from ft. to ft.	Clay, purple to black	106	122
perforations from ft. to ft.	Sand, black & hard shale	122	127
perforations from ft. to ft.	Clay, blue	127	140
perforations from ft. to ft.	Clay, grey	140	147
(8) SCREENS: Well screen installed? ☐ Yes ☐ No	Clay, sandy	147	149
Manufacturer's Name	Sand, black, Med to fine	149	155
e Model No.	Clay, blue	155	<u>158</u>
Diam. Slot size Set from ft. to ft.	Work started 4/27 1966 Completed 5	/10	- 20 6
Diam. Slot size Set from ft. to ft.			19 6
(9) CONSTRUCTION:	Date well drilling machine moved off of well (13) PUMP:	/10	19 6
Well seal—Material used in seal Puddled clay			
Well seal—Material used in seal 2000 OLSY Depth of seal 31 ft. Was a packer used? Yes	Manufacturer's Name		
	Type: H.P.		
	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tyes 1 No Depth	This real was drilled under my invisdiction	and this	nonont i
Was a drive shoe used? ☐ Yes ☐ No Was well gravel packed? ☐ Yes 适 No Size of gravel:	This well was drilled under my jurisdiction true to the best of my knowledge and belief,	and this	report 1
Was well gravel packed? Yes No Size of gravel:	C G Wastanham		
Did any strata contain unusable water? Yes No		ype or print	
Type of water? depth of strata		o, Ore	egon
Method of sealing strata off	Duilling Machine Organizate Livery No.	6	
(10) WATER LEVELS:	Drilling Machine Operator's License No8	,O	••••••
• •	[Signed] C. & Willialing	••••••	
Static level 82 ft. below land surface Date 5/7/66	(Water Well Contractor)	_	_
Artesian pressure lbs. per square inch. Date	Contractor's License No. 86 Date 5/10)	10 66