NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT.
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

CLAC	[15-	13	
State Well	No:	Con		•••
V2532 Per	nit No		*************	-
		*27		

(1) OWNER:	(10) LOCATION OF WELL:			
Name Ed Wilson	County Clackamus Driller's well number			
Address 6845 S Schneider Rd. S	14 14 Section 17 T. 58	R. 7E W.M.		
Canby, Oregon 97013	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):				
New Well ∰ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ااه		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 49	ft.		
Domestic M Industrial Municipal		surface. Date 9/12/80		
Des Bored Irrigation Test Well Other				
	Artesian pressure lbs. per squar	e mcn. Date		
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well b	pelow casing 8		
8 " Diam. from 0 ft. to 202tt. Gage 1/4"	Depth drilled 223 ft. Depth of compl	0.07		
"Diam. fromft. to	Formation: Describe color, texture, grain size a	and structure of materials:		
"Diam. from	and show thickness and nature of each stratus	m and aquifer penetrated,		
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in.	Soil			
perforations fromft, toft.	Brown clay	2 29		
perforations from ft. to ft.	Blue clay	29 44		
perforations fromft. toft.	Cement gravel	44 49		
	Sand & gravel	49 62		
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Blue clay	62 82		
Manufacturer's Name	Blue sandy clay	82 103		
Type Model No.	Blue clay	103 128		
Diam. Slot size	Green clay	128 193		
Diam. Slot size Set from ft. to ft.	Brown clay	193 203		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand with clay streaks	203 223		
pump test made? Yes No If yes, by whom? driller	Green clay	223		
	REULIVED			
ild: 165 gal./min. with 115ft. drawdown after 6 hrs.	act 1.3.1980	T		
" " " " " " " " " " " " " " " " " " "	001 20100			
" " " " " " " " " " " " " " " " " " "	WATER RESOURCES DEPT			
er test gal./min. with ft. drawdown after hrs.	SALEM, OREGON			
tesian flow g.p.m.				
Temperature of water Depth artesian flow encountered ft.	Work started 9/3/80 19 Complete	ed 9/12/80 19		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/13/80 19		
Well seal—Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface toft.	This well was constructed under my			
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to my		
Diameter of well bore below seal	[Signed] John N. Mills	DateQct10., 19.80		
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	_		
How was cement grout placed? <u>pumped</u>	Drilling Machine Operator's License No.			
The second secon	Water Well Contractor's Certification:			
100 mm	This well was drilled under my jurisdi	ction and this report is		
Was a drive shee used? M Vos El No Plusa.	true to the best of my knowledge and bel			
Was a drive shoe used? A Yes No Plugs Size: location ft.	Name John T. Miller	(There		
Did any strata contain unusable water? Yes 25 No	(Person, firm or corporation)	(Type or print)		
Type of water? depth of strata	Address1780TomlinAveWood	purn, Ure		
Method of sealing strata off	[Signed] John A. Mille			
Was well gravel packed? ☐ Yes 🖾 No Size of gravel:	(Water Well Contra			
Gravel placed from ft. to ft.	Contractor's License No277 Date	ct 10 , ₁₉ 80		
(USE ADDITIO	NECESSARY)	- AT-45/(V-)		