NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of the dat

02550State Well No. 5/1-18

of well completion.	dust far, - test is the continue of the	State Permit No		
(1) OWNER:	TER ORTHOR	(11) WELL TESTS: Drawdown is amount lowered below static	water level	is
Name Bill Newby		Was a pump test made? Ves No If yes, by who		
Address Rte 1 Hubbard, Oregon		Yield: gal./min. with ft. drawdov	wn after	hrs.
1,000		" "		,,
				,,
(2) LOCATION OF WELL:		Bailer test 9 gal./min. with 105 ft. drawdo	wn after ?	2 hrs.
County Clcck Driller's well number		Artesian flow g.p.m. Date		
½ ¼ Section T.	R. W.M.	Temperature of water Was a chemical analysis	made? 🗌 Y	es 🗓 No
Bearing and distance from section or subdivis	ion corner		^	
		(12) WELL LOG: Diameter of well below		
		Depth drilled 105 ft. Depth of completed	***************************************	105 ft.
		Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each	ial and struc f the materic change of f	sture, and al in each formation.
		MATERIAL	FROM	то
(3) TYPE OF WORK (check):		Surface	0	2
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐ bandonment, describe material and procedure in Item 12.		Sandy brown clay	2	33
		Sandy blue clay	33	58
	T	Brown sandy clay	58	64
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Blue sandy clay	64	70
Domestic 🙀 Industrial 🗌 Municipal 🗍	Rotary ☐ Driven ☐ Cable 🛱 Jetted ☐	Sandy 6 gpm	70	80
Irrigation Test Well Other	Cable 🖾 Jetted 🗌 Dug 🗍 Bored 🗍	Blue clay	80	85
	1	White clay	85	93
	readed Welded	Blue clay	93	95
8 " Diam. from 0 ft. to	OF ft. Gage	Brown sand 3 gpm	95	103
6 " Diam. from		Blue clay	103	105
" Diam. from ft. to	ft. Gage	•		
(7) PERFORATIONS: Per	forated? 📝 Yes 🗌 No			
Type of perforator used Torch				
Size of perforations in. by	in.			
perforations from	0 80 ft. to ft.			
perforations from9	103 ft. to 103 ft.		_	
perforations from				
perforations from	ft. to ft.		_	
perforations from	ft. to ft.			ł
(0) CODEENS.	-4-11-4 F1 37 Nt 37-		_	
(8) SCREENS: Well screen in	stalled 🗌 Yes 🔀 No			<u> </u>
Canufacturer's Name	odel No			
Diam Slot size Set from		Work started May 7 19 62 Completed	Morr 77	1962
Diam. Slot size Set from ft. to ft.		Work started May / 19 62 Completed Date well drilling machine moved off of well May	May II	1962
			76	1002
(9) CONSTRUCTION:		(13) PUMP:		
·Well seal—Material used in seal Bentonite		Manufacturer's Name Rapidayton		,,
Depth of seal25 ft. Was a packer used?no		Type:Submersible	. н.р/2.	·····
Diameter of well bore to bottom of seal	12 in,	WY / TY 11 Co. 1 - 1 - 1 - C - 12 C - 12 - 12		
Were any loose strata cemented off? ☐ Yes	No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 🗌 Yes 🕱 No	· · · · · · · · · · · · · · · · · · ·	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	a and this	report i
Was well gravel packed? Yes A No Size	e of gravel:			
Gravel placed from ft, to ft,		NAME John Truman Miller (Person, firm or corporation)	(Type or pri	
Did any strata contain unusable water? ☐ Yes 😾 No				
Type of water? Depth of	strata	Address P.O. Box 42 Hubbard	,vrego	(L
Method of sealing strata off		Drilling Machine Operator's License No27.	Z	
(10) WATER LEVELS:		1 72:11		
	surface Date 5/11/62	[Signed] (Water Well Contractor		
,	· /	Contractor's License No. 277 Date Ma		10 62
Artesian pressure lbs. per squ	are inch Date	_ Contractor's License NoL.L Date		, 19