NOTICE TO WATER WELL CONTRACTOR WATER WELL REPORTRECEIVED The original and first copy MAY 1 4 1974 Well No. 55/1E-23 of this report are to be filed with the STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) CLAC(Do)not write above this line) STATE ENGINEER within 30 days from the date of well completion. SALEM OREGON (10) LOCATION OF WELL: (1) OWNER: Crestview Farms Lucht Bress. Rte.3, Box 362 County Claskana Driller's well number Name Mollala reg, 97038 W.M. Address N.E. 4 N.E. 4 Section 23 T. 5.S. R. 1.E Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [Reconditioning | Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Rotary Driven | ft. below land surface. Date Domestic | Industrial | Municipal | Static level Cable Jetted | Dug Bored | Irrigation Test Well Other Artesian pressure lbs. per square inch. Date) CASING INSTALLED: Threaded | Welded (12) WELL LOG: L2 __" Diam. from _____ 6 ____ ft. to ___313 ____ ft. Gage 250 ____ Depth drilled 521 ft. Depth of completed well 520 Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.) PERFORATIONS: Perforated? [] Yes 📆 No. MATERIAL. SWT. pe of perforator used Size of perforations in. by Tenseil <u>5</u>9 Clay brown perforations from ft. to 60 Cemented gravel perforations from ft. to ft. 60 161 Clay brown perforations from ft. to ft. Clay blue sticky (7) SCREENS: Well screen installed? □ Yes Clay brown Manufacturer's Name Sandy elay Crumbly shale Diam. Slot size Set from ft. to Westhered basalt Diam. Slot size Set from asalt black med. ssalt bard Drawdown is amount water level is lowered below static level (8) WELL TESTS: Claystone basalt mixed Basalt grey hard erevisey Was a pump test made ★ Yes □ No If yes, by whom? vesthered keneysemb reck 250 gal./min. with 205 ft. drawdown after 3 hrs. Black and green and brown 516 Basalt grey hard Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. Depth artesian flow encountered ft. pperature of water Work started 3/4 19 74 Completed Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used Gentant * Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Diameter of well bore to bottom of seal _____in. best knowledge and belief. [Signed] Razus Staduly. Date 4/30 1977 (Drilling Machine Operator) Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal ____25_. Brand name of bentonite QUICK GELL Number of pounds of bentonite per 100 gallons Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name R. Stadeli & Sons Inc (Type or print) Was a drive shoe used? ▼ Yes □ No Plugs Size: location ft. Did any strata contain unusable water? 🗌 Yes 🕱 No Type of water? depth of strata Method of sealing strata off

Was well gravel packed? ☐ Yes ☐ No Size of gravel: ...

Gravel placed from ft. to

(Water Well Contractor)