WATER WELL REPORT CE VED The original and first copy of this report are to be STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the State Well No. JAN 2 4 1977 State Permit No. FEB 41977 (Please type of plant)
FEB 41977 (Please type of plant)
FEB A1977 (Please type of plant)
FEB A1977 (Please type of plant)
FEB A1977 (Please type of plant) of well completion. VIATER RESOURCES DEPT. SALEM, COECON SALEM. OREGON (10) LOCATION OF WELL: (1) OWNER: Driller's well number Bernard Kimlinger E. 14 S.E. 14 Section Ox Address Rt 3 box 300 a Molalla searing and distance from section or subdivision corner (2) TYPE OF WORK (check): Abandon [7] Deepening [Reconditioning [New Well If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): Depth at which water was first found (3) TYPE OF WELL: ft. below land surface. Date 1-18- 77 Domestic 🕱 Industrial 🗌 Municipal 🗍 Rotary Driven Static level 37 Cable Jetted [lbs. per square inch. Date Irrigation Test Well
Other Artesian pressure Bored | Dug CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing " Diam, from 0 ft. to 72 ft. Gage 250 ft. Depth of completed well 163 Depth drilled 163 " Diam. from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, ." Diam. from ft. to ft. Gage with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes No. MATERIAL pe of perforator used 0 Top soil ban Size of perforations in. by 19 Clay ban perforations from ft. to ft. 27 19 Broken rock grey ... perforations from ft. to ft. 41 clay grey perforations from _____ ft. to _____ ft. 41 98 M. Claystone 98 128 H. Basalt grey (7) SCREENS: Well screen installed?

Yes
No 128 132 M.H. Seamy Basalt Manufacturer's Name 132 H. Basalt grey 163 Diam. Slot size Set from ft. to ft. S. Claystone grey Diam. Slot size Set from ft. to ft. Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made?
Yes No If yes, by whom? hrs. ft. drawdown after gal./min. with Yield: Baller test 75 gal./min. with 95 ft. drawdown after 3 g.p.m. Artesian flow 1977 1-8 19 77 Completed Work started Depth artesian flow encountered ft. nperature of water 19 77 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material usedcement This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to ______50 Diameter of well bore to bottom of seal 10 in. Bate 1-21 1977 Diameter of well bore below seal in. (Drilling Machine Or Drilling Machine Operator's License No. 84 Number of sacks of cement used in well seal Number of sacks of bentonite used in well seal Water Well Contractor's Certification: Brand name of bentonite Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is 1bs./100 gals. true to the best of my knowledge and belief. Stadelti Drilling Company (Type or print) Was a drive shoe used?

Yes No Plugs Size: location ft. Did any strata contain unusable water? 🗌 Yes 🛣 No depth of strata Type of water? Method of sealing strata off Was well gravel packed? ☐ Yes [No Size of gravel: Contractor's License No. 519 Date 1-2 Gravel placed from ft. to

NOTICE TO WATER WELL CONTRACTOR