

RECEIVED

CLAC
02688

5/1-29 B

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

MAY 20 1968 WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310
STATE ENGINEER, STATE OF OREGON
SALEM, OREGON (Please type or print)
within 30 days from the date of well completion. (Do not write above this line)

State Well No. 5/1-29 B
State Permit No.

(1) OWNER:

Name John Beck
Address Route 2, Box 183, Woodburn, Ore

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
" Diam. from 0 ft. to 19 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 27 ft. below land surface Date 4-6-68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test NONE gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Bentonite
Depth of seal 18 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel 3/8-3/4
Gravel placed from 0 ft. to 95 ft. 8 yds.

(11) LOCATION OF WELL:

County Clackamas Driller's well number
Bearing and distance from section or subdivision corner
2500 ft W. 200 ft S. of N.E. cor of sec 29 . T.5S. R.1E.

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 95 ft. Depth of completed well 0 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Original well was drilled by WILLIAMATTE DRILLING CO, 1965.			
There well log read as follows,			
Top soil.	0	2	
Brn clay.	2	15	
Black sand, silty.	15	20	
Grey clay.	20	40	
Brn clay with gravel.	40	60	
Blue clay with gravel.	60	80	
Brn clay wt	80	100	
Red clay.	100	110	
Grey clay.	110	135	
Black sand & grey clay.	135	140	
Grey clay.	140	180	

We drilled 6" hole on S. side of casing down to 95 ft. Filled with 3/8-3/4 round gravel, and pulled casing back to 19 ft. We also swabed the original well.

Work started 4-1-68 19 Completed 4-6-68 19
Date well drilling machine moved off of well 4-6-68 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ben [Signature] Date 4-6-68 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 322

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME R. Stadel & Sons
(Person, firm or corporation) (Type or print)
Address Route 3, Box 169, Silverton, Ore.
[Signed] Paul R. Stadel
(Water Well Contractor)
Contractor's License No. 296 Date 5-10, 1968