

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion

RECEIVED DEC 3 1968 STATE ENGINEER SALEM, OREGON

STATE OF OREGON

(Please type or print) (Do not write above this line)

CLAC 02699

State Well No. 5/1E-29abb

State Permit No.

G-4763

(1) OWNER:

Name John Beak Address Rt 2 Box 183, Woodburn

(2) TYPE OF WORK (check):

New Well [ ] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [ ] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [x] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

10" Diam. from 0 ft. to bottom except for screens Gage 250

(6) PERFORATIONS:

Type of perforator used Torch Perforated? [x] Yes [ ] No Size of perforations 3/8 in. 250 260

(7) SCREENS:

Well screen installed? [x] Yes [ ] No Manufacturer's Name Johnson Type Irrigator Model No. 100 Diam. 10 Slot size 100 Set from 25 ft. to 55 ft.

(8) WATER LEVEL: Completed well.

Static level 38 ft. below land surface Date 11/15 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [x] Yes [ ] No If yes, by whom? Driller Rate: 200 gal./min. with 171 ft. drawdown after 5 hrs.

(10) CONSTRUCTION:

Well seal—Material used cement Depth of seal 20 ft. Diameter of well bore to bottom of seal 25 in. Were any loose strata cemented off? [ ] Yes [x] No Depth Was a drive shoe used? [ ] Yes [x] No Did any strata contain unusable water? [ ] Yes [ ] No Type of water depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [ ] No Size of gravel 3/8" Pea Gravel placed from 0 ft. to 260 ft.

(11) LOCATION OF WELL:

County Clackamas Driller's well number 1/4 Section T. R. W.M.

Bearing and distance from section or subdivision corner 2600' W. & 580'S of N.E. cor Sec 29 T5S R1E Drilled 8" to 327 & 19" to 260

(12) WELL LOG:

Diameter of well below casing none Depth drilled 327 ft. Depth of completed well 260 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil brn, Clay brn, Fine sand, Clay brn, Dirty sand grey fine, Dirty sand grey fine, Med sand & gravel brn W.B., Course sand brn W.B., Clay brn, Clay sandy grey, Clay brn, Clay sandy grey, Med sand dirty, grey W.B., Clay grey, Fine sand grey W.B., Clay grey, M. sand grey W.B., Clay grey.

Work started 10/28 1968 Completed 11/15 68 Date well drilling machine moved off of well 11/15 68 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] C.E. Stadel Date 11/18 68 (Drilling Machine Operator)

Drilling Machine Operator's License No. 84

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME R. Stadel & Sons (Person, firm or corporation) (Type or print) Silverton, Oreg.

Address [Signed] Paul R. Stadel (Water Well Contractor)

Contractor's License No. 296 Date 11/18 68