

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

CLAC 02735

Rec. WRD 4/13/84 CW

State Well No. 55/E-32d

State Permit No.

OWNER:

Name Lyle Landsem Address Rt 2 Box 215, Woodburn, Oreg.

(2) TYPE OF WORK (check):

New Well [] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [x] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x] Diam. from 0 ft. to 182 ft. Gage 250

(6) PERFORATIONS:

Type of perforator used Size perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Driller Yield: 500 gal./min. with 112 ft. drawdown after 4 hrs.

(9) CONSTRUCTION:

Well seal-Material used Bentonite Well sealed from land surface to 180 Diameter of well bore to bottom of seal 12" to 20" 10" to 180 Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal 6 sacks Brand name of bentonite Quik Gel Number of pounds of bentonite per 100 gallons of water 25 lbs./100 gals Was a drive shoe used? [] Yes [x] No Plugs Size: location ft. Do any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 1/4 SE 1/4 Section 32 T. 55 R. 1E - W.M. Bearing and distance from section or subdivision corner 1900' W. & 200' N. of S.E. COR SEC 32, T. 55, R. 1E.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 25 ft. Static level 70 ft. below land surface. Date 8/ Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8" Depth drilled 300 ft. Depth of completed well 300 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Top soil brn., Clay brn., Red conglomerate brn. W.B., Clay brn., Clay grey, Red Conglom. grey, Clay grey yellow, Fine sand grey W.B., Sandstone grey W.B. (most water coming)

Work started 8/3 19 70 Completed 8/21 19 70 Date well drilling machine moved off of well 9/11 19 70

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] C. L. Stadel Date 9/7/70 19 70 (Drilling Machine Operator)

Drilling Machine Operator's License No. 84

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name H. Stadel & Sons (Person, firm or corporation) (Type or print)

Address Rt. 3, Silverton, Oreg

[Signed] Paul R. Stadel (Water Well Contractor)

Contractor's License No. 236 Date 9/7/70 19 70