## STATE OF OREGON RECEIVED WATER WELL REPORT (as required by ORS 537.765) JAN 0 8 1986

JAN 0 & 1986 PLEASE TYPE of PRINT IN INK

(as required by One 557.700) OTHER OF PLEASE 11PE OF	(for official use only)
(1) OWNER: WATER RESOURCES DEPT	(10) LOCATION OF WELL by legal description:
ADE Abouterans	County Clackanas NE 1/4 NE 1/4 of Section 32 of
Name Roma J. Vosgien Address 7916 Monte Cristo Rd.	
City Woodburn State OR . 97071	(Township is North or South) (Range is East or West)
	Tax Lot Lot Block Subdivision  MAULING ADDRESS OF WELL (or nearest address)
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
New Well Deepening Reconditioning Abandon A	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL of COMPLETED WELL:
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 84 ft.
Rotary Air 🗷 Driven 🗆 Domestic 🍱 Industrial 🗆 Municipal 🗆 Thermal:	Static level 42 ft. below land surface. Date 12-114-8
Rotary Mud Dug Irrigation Withdrawal Reinjection Other:	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	
CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing
Threaded $\square$ Welded $\square$	Formation: Describe color, texture, grain size and structure of materials; and show thickness
6 Diam. from +1 ft. to 126 ft. Gauge•250	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
TDiam. from	water-bearing strata.
LINER INSTALLED: Steel  Plastic	MATERIAL From To SWL
Threaded  Welded	Top Soil 0 1
" Diam. from ft. to ft. Gauge	Clay 1 8
(6) PERFORATIONS: Perforated? <b>X</b> Yes □ No	Rock 8 15
Size of perforations in. by 2 in.	Clay 15 8h
300 perforations from 81 ft. to 101 ft.	Clay with seams of sand 8h 10h 42
perforations from ft. to ft.	Clay 10h 126
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes ■ No	
Manufacturer's Name	
Type	
Diam Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft. to ft.	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	
Was a pump test made?	
d: gal./min. with ft. drawdown after hrs.	
, , , , , , , , , , , , , , , , , , ,	
Air test 7 gal./min. with drill stem at 94 ft. 3 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	Date work started 11-27-85 /completed 12-11-85
CONSTRUCTION: Special standards: Yes $\square$ No $\blacksquare$	Date well drilling machine moved off of well 12-16 19 85
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.
Diameter of well bore below seal10 in.	[Signed]
Amount of sealing material	
How was cement grout placed? Bentonite was poured	(bonded) Water Well Constructor Certification:
	Bond 9197179 Issued by: Fidelity & Deposit Co. (Surety Company Name)
Was pump installed? Type	On behalf of Donnelly Drilling Co. (type or print name of Water Well Constructor)
Was a drive shoe used?   Yes No Plugs Size: location ft.	(type or print name or Water Well Constructor)
Did any strata contain unusable water?  Yes No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed) (Water Well Constructor)
Was well gravel packed? Yes No Size of gravel: 3/8 X3/4	(Dated)12-26-85
Gravel placed from	(Dated)