

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

RECEIVED CLAC WATER WELL REPORT 03106 JUL 15 1969 STATE OF OREGON WELL No 2

State Well No. 211-16 bd

State Permit No.

(1) OWNER:

Name LAKE OSWEGO HIGH SCHOOL Address 2455 SW COUNTRY CLUB ROAD LAKE OSWEGO ORE.

(11) LOCATION OF WELL:

County CLACK Driller's well number 5314 SE 1/4 NW 1/4 Section 16 T. 25 R. 1E W.M.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [] Test Well [] Other [X]

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 8 Depth drilled 722 ft. Depth of completed well 722 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Content: SEE ATTACHED SHEET

CASING INSTALLED:

8" Diam. from 0 ft. to 108 ft. Gage 277

PERFORATIONS:

Perforated? [] Yes [X] No.

Type of perforator used

Table with columns: Size of perforations, in. by, in. Rows for perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 389 ft. below land surface Date 6/26/69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? STRASSER

Flow: 190 gal./min. with 111 ft. drawdown after 10 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 56 Was a chemical analysis made? [X] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used CEMENT GROUT Depth of seal 0-20 90-102 ft.

Diameter of well bore to bottom of seal 1.0 in.

Were any loose strata cemented off? [] Yes [X] No Depth

Was a drive shoe used? [] Yes [X] No

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

Work started MAY 13 1969 Completed JULY 3 1969

Date well drilling machine moved off of well JULY 5 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] B. Mackenzie Date JULY 9 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 543 190

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME R.J. STRASSER DRILLING CO (Person, firm or corporation) (Type or print)

Address 8110 SE SUNSET LANE PORTLAND ORE

[Signed] Robert L. Strasser (Water Well Contractor)

Contractor's License No. 10 Date JULY 11 1969

2s/1e-16bd

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane
Portland, Oregon 97206

July 11, 1969

Log of well no. 2 Lake Oswego High School

yellow and brown clay	0 - 16
yellow orange clay	16 - 28
brown clay	28 - 38
sandstone	38 - 46
decomposed lava	46 - 98
Medium hard grey basalt	98 - 114
hard grey basalt	114 - 120
grey sandstone	120 - 144
brown and grey sandstone	144 - 153
conglomerate	153 - 158
grey porous basalt	158 - 162
conglomerate	162 - 165
broken grey and brown basalt	165 - 188
porous brown and grey basalt	188 - 218
brown and grey basalt, some clay seams	218 - 231
brown sandstone	231 - 235
grey basalt	235 - 276
red porous lava	276 - 278
porous grey and brown basalt	278 - 284
hard grey basalt	284 - 289
brown cracked basalt	289 - 298
hard grey basalt	298 - 313
brown and grey basalt	313 - 318
soft porous red lava	318 - 328
hard grey basalt	328 - 364
medium hard cracked grey and brown basalt	364 - 388
hard grey basalt	388 - 430
cracked grey basalt	430 - 435
hard grey basalt	435 - 491
red clay and brown basalt	491 - 494
brown porous basalt	494 - 497
medium hard grey porous basalt	497 - 499
hard grey basalt	499 - 523
brown broken basalt and yellow zeolite	523 - 525
brown and red basalt	525 - 546
hard grey basalt	546 - 565
brown and grey cracked basalt	565 - 567
red and brown basalt	567 - 573
porous brown basalt	573 - 584
medium hard grey basalt	584 - 594
weathered brown basalt	594 - 604
hard grey basalt	604 - 649
weathered brown basalt	649 - 670
grey basalt	670 - 673

RECEIVED
JUL 15 1969
STATE ENGINEER
OREGON

2s/1ε-166d

hard brown basalt
medium hard brown basalt
hard black basalt
medium hard brown basalt
hard black basalt

673 - 683
683 - 688
688 - 694
694 - 717
717 - 722

RECEIVED
JUL 15 1969
STATE ENGINEER
SALEM OREGON