RECEIVED 25/18-200

STATE OF OREGON (3100)	SEP1 6 1985
WATER WELL REPORT	
(as required by ORS 537.765) PLEASE TYPE o	PRINT IN INK WATER RESOURCES DEPT
	CALEM OREGON
(1) OWNER: 639-8168	(10) LOCATION OF WELL by legal description:
TANK BARAK	County CLACKAMAS 4 4 of Section 20C of
100 mg	Township 23 , Range 1E , WM.
000 000000	(Township is North or South) (Range is East or West)
City LAKE OSWEGO State OREGON	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
· · · · · · · · · · · · · · · · · · ·	
New Well A Deepening Reconditioning Abandon Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL of COMPLETED WELL:
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary Air Driven Domestic Industrial Municipal D	Depth at which water was first found 310
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 95 ft. below land surface. Date 8/7/8
Other:	Artesian pressure lbs. per square inch. Date
Cable Bored D Piezometric D Grounding D Test	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic Q.	Depth drilled 365 ft. Depth of completed well 365 ft
(5) CASING INSTALLED: Steel Plastic Threaded Welded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness
6 Diam from +1 ft. to 340 ft. Gauge . 250"	and nature of each stratum and aquifer penetrated, with at least one entry for each change of
"Diam. from	formation. Report each change in position of Static Water Level and indicate principal
	water-bearing strata.
LINER INSTALLED: Steel Plastic Plastic Welded Welded	MATERIAL From To SWL
	TOP SOIL 0 2
" Diam. from	BROWN CLAY 2 40
(6) PERFORATIONS: Perforated? ☐ Yes 🕱 No	BROWN SANDY CLAY 40 86
Size of perforations in. by in.	FINE BROWN SAND 86 97
perforations from ft. to ft.	1100
perforations from	
perforations from ft. to ft.	SOFT BLUE SAND-
(7) SCREENS: Well screen installed? Yes A No	STONE (49.P.M.) 310 319 160
Manufacturer's Name	BLUE CLAY 319 326
TypeModel No	BROWN DELOMPOSED
Diam. Slot Size Set from ft. to ft.	BASALT 326 335
Diam Slot Size Set from ft. to ft.	SOFT BROWN BASALT 335 360 95
Drawdown is amount water level is lowered	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 🏿 No If yes, by whom?	
ield: gal./min. with ft. drawdown after hrs.	# 597
	H 014
Air test gal./min. with drill stem at ft. hrs.	
Bailer test 20 gal./min. with 200 ft. drawdown after hrs.	
Artesian flow g.p.m.	
emperature of water Depth artesian flow encountered ft.	Data work started 7/5/85 /completed 8/1/85
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date work started
COALCAIT / COL REALTING II THE	Date well drilling machine moved off of well 9/7/ 19 &
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	10
Amount of sealing material sacks pounds	[Signed] Date19
How was cement grout placed? PUMPED, A SACKS OF	(bonded) Water Well Constructor Certification:
CEMENT FORCED AROUND BOTTOM	Bond Issued by:
OF CASING TO PREVENT LEAKAGE	(number) (Surety Company Name)
Was pump installed? Type	On behalf of Kaler WELL KILLING CO.
West a drive shoe used? Yes \(No. Plugs Size location	(type or print name of Water Well Constructor)

NOTICE TO WATER WELL CONSTRUCTOR

Size of gravel:

☐ Yes ☐ No

depth of strata

No No

☐ Yes

Did any strata contain unusable water?

Type of Water?

Method of sealing strata off

Was well gravel packed?

Gravel placed from

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

best of my knowledge and belief:

(Signed)

(Dated) ..

This well was drilled under my jurisdiction and this report is true to the

Well Constructor)

SP*46866-690