## WATER WELL REPORT STATE OF OREGON

03164

PECEIVED

_	/
State Well No.	1/E-20
, /	

CLAC

FEB 2 1983

WATER RESOURCES DEPT. State Permit No.

Dhandonad

(1) OWNER: City of Rivergrove for the	(10) LOCATION OF WELL:
Name ' Rivergrove Water Dist. Well No 3	County CLACKAMAS Driller's well number
Address 7725 SW Boones Ferry Road	4 4 Section 20 T. 28 R. IR. W.M.
City Lake Owwego. Oregon State 97034	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location:
New Well □ Deepening □ Reconditioning □ Abandon ■	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
	Static level ft. below land surface. Date
Rotary Mud	Artesian pressure Ibs. per square inch. Date
Bored   Thermal: Withdrawal   Reinjection	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel   Plastic   Plastic	Perty drilled ABANDONMENT ft. Depth of completed well ft.
Threaded □ Welded □	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
"Diam from ft. to ft. Gauge"  Diam from ft. to ft. Gauge	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED:	
	MATERIAL From To SWL
ft. Gauge	JANUARY 1983
(6) PERFORATIONS: Perforated? □ Yes □ No	26th Filled Well Casing the (10") From
Type of perforator used	10 ft. below surface to bottom 480ft)
	7th.with clean silt loam/fine sandy loam (10 plus cu.yds)
ft. to	27th. Excavated around the casing to a
perforations from	depth of 8 to 9 feet
perforations from ft. to ft.	27th.Cut off casing (3 Lavers) at
(1) SCREENS: Well screen installed? Yes No	approximately 8 feet below land
Manufacturer's Name	surface.
Type	7th. Placed Concrete Plug (approx. 3ft.)
Diam. Slot Size Set from ft. to ft.  Slot Size ft. Set from ft. to ft.	at top of casing and around outside
	of casing.
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	27th.Back filled, compacted and mounded
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	excavation site with native material
gal/min. with ft. drawdown after hrs.	and remaining silt loam.
TH H H	HAAKON BOTTNER WAS AT THE SITE
Air test gal./min. with drill stem at ft, hrs.	AT THE COMPLETION
Bailer test gal./min. with ft. drawdown after hrs.	A STATE OF THE STA
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 19 Completed 19
(9) CONSTRUCTION: Special standards: Yes \( \text{No} \( \text{No} \)	Date well drilling machine moved off of well 19
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.  Number of sacks of cement used in well sealsacks	[Signed] Date , 19
How was cement grout placed?	Drilling Machine Operator's License No.
Han the Hand to the Control of the C	Water Well Contractor's Certification:
The state of the s	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.
Was a drive shoe used? 🗆 Yes 🖂 No Plugs Size: location ft.	Name HAAKON BOTTNER DRILLING CO. (Type or print)
Did any strata contain unusable water?   Yes   No	Address 10230 S.E. CINDY LANE, BORING, OR. 97009
Type of Water? depth of strata	
Method of sealing strata off  Was well gravel packed? □ Yes □ No Size of gravel:	[Signed] January (Water Well Contractor)
Was well gravel packed? □ Yes □ No Size of gravel:	Contractor's License No. 109 Date Jan. 31st. , 1983
E Lb.	