NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## E WATER-WELL REPORT

18/ZE - 27CC State Permit No.

JUN 1(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:			
Name RICHARD J. BECK	County CLACKAMAS Driller's well number			
Address 10300 SE CHAMPAGNE IN	Sw 14 Sw 14 Section 27 T. 15	R. 2	F	W.M.
PORTLAND OREGON 97264	Bearing and distance from section or subdivis			
(2) TYPE OF WORK (check):			-	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zall		•
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
				ft.
Cable Jetted   Domestic Industrial   Municipal	Static level 492 ft. below land	surface.	Date ///	821,1419
Dug   Bored   Irrigation 2 Test Well   Other	Artesian pressure lbs. per squa	re inch.	Date	
CASING INSTALLED: Threaded Welded W  8 "Diam from 6 ft to 58 ft Gage 625  7 "Diam from 270 ft to 510 ft Gage 188	(12) WELL LOG: Diameter of well below casing			
PERFORATIONS: Perforated? Yes \( \sigma \) No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used TORCH	MATERIAL	From	то	SWL
Size of perforations 3 in. by 1/4 in.	RED CLAY W/ GRAVEL	0	12	
47 perforations from 492 ft. to 509 ft.	CLAY, BROWN	12	34	
50 perforations from 511 ft. to 529 ft.	Rock, Res	34	87	
perforations fromft. toft.	ROCK VESICULAR RED SOFT	87	90	
(7) COPENC.	Rock RED	90	105	
(7) SCREENS: Well screen installed?   Yes PNo	ROCK BLACK BASALT	105	11 (	ļ <u>.</u>
Manufacturer's Name	Rock, RED	111	190	
Type Model No	Rock, GREY	190	212	
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.	Rock, RED	212	300	
Diani. Stot size Set Holl It. W It.	CLIPY, Gray W/ Gravel	300	367	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CLAY YELLOW W/Gravel	367	414	
	Sand & Gravel, Grey	507	507 532	492
Was a pump test made?  Yes No If yes, by whom?	SANO CUPATE	301	عر د	772
Yield: gal./min. with ft. drawdown after hrs.				
	-			
" " " "				
Bailer test 20 gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.		<u> </u>		
perature of water 52 Depth artesian flow encountered ft.	Work started DEC 17, 19 78 Complete	ed MA	Y21	1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well	MAY	22	1979
Well seal-Material used CEMENT	Drilling Machine Operator's Certification	· ·		
Well sealed from land surface toft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal in.	Materials used and information reported best knowledge and belief.	above	are true	to my
Diameter of well bore below seal in.	[Signed] Lichary & Seck	Date /	14429	7, 19.79
Number of sacks of cement used in well seal 27 sacks	(Drilling Mackine Operator)	4 555	_/	.,
How was cement grout placed? Poured 28Dec 78	Drilling Machine Operator's License No.	LCSLC	<i></i>	
` .	Water Well Contractor's Certification:	•		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes \( \) No Plugs Size: location ft.  Did any strata contain unusable water \( \) Yes \( \) Yo	Name JWBeck Welldrilling			
Type of water? depth of strata	(Person, firm or corporation) Address 24437 35K4/2ne	? 17m	ope of pri	nt)
Method of sealing strata off		P.		
Was well gravel packed? ☐ Yes W No Size of gravel:	[Signed] (Water Well Cont	ractor)		*******
Gravel placed from ft. to ft.	Contractor's License No. 14.49 Date	man	20	10 79
II, IO	1 Contractor & Literise No. K.L. F.J. Date	4.L.MJ.	~~~/	, 18