e to water well contract RECEVATE DELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

MARO 7 1575TE OF OREGON (Please type or print)

Permit No.

SWELL No. LS DE-28ah

within 30 days from the date of well completion.

WATER RESOURCES WDERTove this line) SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name A.F. Pearson Mobile Club	County Clackamas Driller's well number 31-59
Address Portland, Oregon 97266	NW NE A Section 28 T. 1S R. 2E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
** *** *** *** *** *** *** *** *** ***	_ tax lot 2 and 17
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12. (3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Cable	Static level ft. below land surface. Date
Dug	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
"Diam. from	Depth drilled ft. Depth of completed well ft.
"Diam from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated?	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	2700 10 340
perforations from ft. to ft.	We as Aqua Pump Company
perforations from ft. to ft.	
perforations from ft. to ft.	extended the casing that was about
(7) SCREENS: Well screen installed? I Vog II Vog	3 ft. below the ground to 18" above
Manufacturer's Name	the ground.
TypeModel No.	The XXXX original seal that was placed
Diam. Slot size Set from ft. to ft.	in well when drilled is unknown but
Diam Slot size Set from ft. to ft.	was not disturbed then filled with
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	cement from 3 ft. below ground to sur
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	The system was replumbed to the stand-
"	ards of the State of Oregon for mobile
" " " "	home parks
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 19 Completed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin,	
Number of sacks of cement used in well seal sacks	[Signed] Date, 19
How was cement grout placed?	Drilling Machine Operator's License No.
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this well
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief. Name Name Name
Did any strata contain unusable water? Yes No	Name Barron firm or company, Inc.
Type of water? depth of strata	Address 399 SE Walnut Canby, (Type or print) 97013
Method of sealing strata off	/// // Ma a
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	407
it.	Contractor's License No. 497 Date 3-5-79