NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be WATER WELL	RECEIVED REPORT OREGON APR 1 0 1974 State Well No. 25 15	=-27 ba	
STATE OF C	pregon APR 1 0 1974 state Well No. 2011 Spor print) STATE ENGINEERState Permit No.	94.1	
within 30 days from the date of well completion. (D) not write about	ve this linSALEM. OREGON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name REGENT INVESTMENT CO	County CLACK, Driller's well number	5472	
Address 26/1 5.W. 38 AVE	NE 1 NN 1 Section 27 T. 25 R. /E W.M.		
PORTLAND ORE.	Bearing and distance from section or subdivision corner	T	
(2) TYPE OF WORK (check):			
New Well 🙀 Deepening 🗆 Reconditioning 🗀 Abandon 🖂			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 294 ft.		
Rotary Driven Domestic D Industrial D Municipal D	Static level 3/8 ft. below land surface. Date 4/1/74		
Cable	Artesian pressure lbs. per square inch. Date		
6) CASING INSTALLED: Threaded Welded	(40) YVIVI I I OC	9	
8) CASING INSTALLED: Threaded Welded 8 8 10 10 10 10 10 10	(12) WELL LOG: Diameter of well below casing		
"Diam, from ft. to ft. Gage	Depth drilled 638 ft. Depth of completed well 638 ft.		
	Formation: Describe color, texture, grain size and structure and show thickness and nature of each stratum and aqui	re of materials; ifer penetrated,	
	with at least one entry for each change of formation. Report position of Static Water Level and indicate principal water	t each change in	
Perforated? Tyes No.			
Type of perforator used	MATERIAL From	To SWL	
Size of perforations in. by in.	SEE ATTACHED SHE	=7	
perforations from ft. to ft.		-	
perforations from ft. to ft.			
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? Yes X No			
Manufacturer's Name			
Type Model No.			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft, to ft.		:	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)			
Yield: 260 gal./min. with //3ft. drawdown after /7 hrs.			
200 " 84 " 23"			
<u>")75 " 18 " L¢"</u>	the district the second		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.	7-12 - 74/ 17-	74	
nperature of water 5 Depth artesian flow encounteredft.	Work started 7-63 5 19 4 Completed 44D	2 4 19 74	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2 4 19 / 4	
Well seal-Material used No 8 MESH BENTONITE	Drilling Machine Operator's Certification:	aunonviaion	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal	best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] Could School Date APR 5, 1974		
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 3.64	-	
Brand name of bentonite		4,1 4	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name RJ STRASSER DRILLING (0		
Did any strata contain unusable water? Yes \(\subseteq \text{No} \)	(Person, firm or corporation) (Type or print)		
Type of water? ABOVE STATIC depth of strata 35% 358 Method of sealing strata off CEMENT GROUT AND	Play I there		
Was well gravel packed? ☐ Yes V No Size of gravel:	[Signed] (Water Well Contractor)		
Gravel placed fromft_toft.	Contractor's License No. 10 Date 19PR	5, 1979	

Phone: 771-2355

R. J. Strasser Drilling Co.

8110 S. E. Sunset Lane Portland, Oregon 97206

April 8, 1974

RECEIVED

APR 1 0 1974 STATE ENGINEER SALEM, OREGON

Log of test well for Regent Investment Co.
Oswego Greens

top soil	0 - 4
broken brown basalt	4 - 18
black basalt	18 - 41
soft brown basalt	41 - 90
medium hard black basalt	90 - 98
brown basalt	98 - 116
black basalt	116 - 143
brown basalt	143 - 170
black basalt	170 - 225
hard grey basalt	225 - 261
brown basalt	261 - 281
black basalt	281 - 294
broken black basalt	294 - 300
hard grey basalt	300 - 354
broken grey basalt	354 - 358
black basalt	358 - 375
brown basalt	375 - 389
hard grey basalt	389 - 435
broken grey basalt	435 - 462
black basalt	462 - 498
broken, brown basalt	498 - 524
medium hard black basalt	524 - 534
porous black basalt	534 - 541
hard grey basalt	541 - 628
broken black basalt	628 - 633
hard black basalt	633 - 638