STATE ENGINEER Salem, Oregon CLAC 100347	ecord	STATE WELL NO. 1S/2-29E COUNTY Clackamas APPLICATION NO. GR-3006
OWNER: Vernon W. Schuld, dba Bell Sand &	ADDRESS: .	6435 SE Johnson Creek Blvd.
LOCATION OF WELL: Owner's No		Portland 6, Oregon
SW 1/4 NW 1/4 Sec. 29 T. 1 S., R. 2 W., V. Bearing and distance from section or subdivision  corner 900' E. and 1210' N. from W. Corner  Hector Campbell DLC 41		
Altitude at well		
TYPE OF WELLdrilled Date Constructed 1937.  Depth drilled Depth cased 147'  Depth cased 147'		Section
CASING RECORD:		
FINISH:  40 per foot 3/8 x 1/2, 8 rows from 130	to 143	
AQUIFERS:		
Sand, boulders, clay, gravel	• page 1800	
WATER LEVEL: 35'		,
PUMPING EQUIPMENT: Type Sterling DW Capacity 350 G.P.M.		H.P. 10
WELL TESTS: Drawdown 57 ft. after h		
Drawdown 45 ft. after h	ours pump	oing 195 G.P.M.
USE OF WATER industrial T SOURCE OF INFORMATION GR-2815 DRILLER or DIGGER		·
ADDITIONAL DATA:  Log	Chemical An	nalysis Aquifer Test

REMARKS:

## STATE ENGINEER Salem, Oregon

State	Well	No.	1S/2/29E		
County Cl			Lackamas		
	-		GR-3006		

## Well Log

er:	(Feet below	Thickne	
	From	То	(feet
Sand	11	121/2	
Boulders and clay	121/2	16	
Sand	16	20	
Coarse sand and gravel	20	38	
Fine sand	38	43	
Some water and coarse sand	43	69	
Yellow clay	69	72	
Blue Clay	72	78	
Some gravel and water	78	85	
Yellow Clay and gravel	85	95	
Cemented gravel	95	110	
Some sand and gravel and water	110	118	
Solid gravel	118	129	
Loose gravel and water	129	3.);7	
,			
ţ.			